

THIS REPORT HAS BEEN DELIMITED  
AND CLEARED FOR PUBLIC RELEASE  
UNDER DOD DIRECTIVE 5200.20 AND  
NO RESTRICTIONS ARE IMPOSED UPON  
ITS USE AND DISCLOSURE.

DISTRIBUTION STATEMENT A

APPROVED FOR PUBLIC RELEASE;  
DISTRIBUTION UNLIMITED.

**AD**

**80006**

# **Armed Services Technical Information Agency**

**Reproduced by**  
**DOCUMENT SERVICE CENTER**  
**KNOTT BUILDING, DAYTON, 2, OHIO**

This document is the property of the United States Government. It is furnished for the duration of the contract and shall be returned when no longer required, or upon recall by ASTIA to the following address:  
Armed Services Technical Information Agency, Document Service Center,  
Knott Building, Dayton 2, Ohio.

**NOTICE: WHEN GOVERNMENT OR OTHER DRAWINGS, SPECIFICATIONS OR OTHER DATA ARE USED FOR ANY PURPOSE OTHER THAN IN CONNECTION WITH A DEFINITELY RELATED GOVERNMENT PROCUREMENT OPERATION, THE U. S. GOVERNMENT THEREBY INCURS NO RESPONSIBILITY, NOR ANY OBLIGATION WHATSOEVER; AND THE FACT THAT THE GOVERNMENT MAY HAVE FORMULATED, FURNISHED, OR IN ANY WAY SUPPLIED THE SAID DRAWINGS, SPECIFICATIONS, OR OTHER DATA IS NOT TO BE REGARDED BY IMPLICATION OR OTHERWISE AS IN ANY MANNER LICENSING THE HOLDER OR ANY OTHER PERSON OR CORPORATION, OR CONVEYING ANY RIGHTS OR PERMISSION TO MANUFACTURE, USE OR SELL ANY PATENTED INVENTION THAT MAY IN ANY WAY BE RELATED THERETO.**

**UNCLASSIFIED**

SMiller/mcd/7118


SP  
FA 319.1/30 2100 SL

SUBJECT: Correction to Final Summary Report for Contract DA-36-038-ORD-14091 - Heintz Manufacturing Company

TO: Armed Services Technical Information Agency  
Document Service Center  
Knott Building  
Dayton 2, Ohio

There are forwarded herewith five corrected copies of Page 14 of the Final Summary Report on the Development, Manufacture and Metallurgical Study of a Cold Extrusion Process for the Manufacture of 30mm Projectile Bodies, prepared by the Heintz Manufacturing Company on work performed by them under Contract DA-36-038-ORD-14091. These corrected copies should be inserted in the proper place in each summary report and the original Pages 14 destroyed.

FOR THE COMMANDING GENERAL:



1 Incl (5 cys)  
Pg. 14 of Summary Rpt

ALFRED S. HITNER  
Assistant

**SUMMARY REPORT**

on

**DEVELOPMENT, MANUFACTURE and METALLURGICAL STUDY**

**of the**

**PROJECTILE, PRACTICE, 30MM, T304**

**PROJECTILE, PRACTICE, 30MM, T241**

**PROJECTILE, TARGET PRACTICE, 30MM, T328**

**SHELL, H.E.L., 30MM, T306E10**

**HEINTZ MANUFACTURING COMPANY**

**Steelprest**

**PHILADELPHIA 20, PA.**

80006



# HEINTZ MANUFACTURING COMPANY

FRONT STREET & OLNEY AVE.

Steelpress

PHILADELPHIA 20 • PENNA.

October, 1955

Commanding General  
Frankford Arsenal  
Bridge & Tacony Streets  
Philadelphia 37 Pennsylvania

FC

Re Report on 30mm Shell  
Contract DA-36-038-ORD-14091

Dear Sir

We are pleased to hand you herewith the detailed record of the development, manufacture and examination of 30mm projectiles of four types--all made by cold forming operations including cold extrusion.

That cold forming is the recommended way to make good and cheap shell of such size is conclusively shown not only in this report but in our earlier experience in making other 30mm projectiles for Picatinny Arsenal and an European customer.

Strength requirement--90,000 psi minimum yield--was met with a liberal margin and with a useful amount of ductility.

Firing results were "uneventful", according to informal word.

Tonnages noted in making these shell, ranged from a top of 105 on T304, 118 on T328, 159 on T241 and 233 on T306E10 and down to 10 tons. These developmental loads would be reduced by operational and minor design changes. Tool life accordingly would be expected to be satisfactorily very high. Presses desirable in a production line are described in the Appendix.

Facilities to produce up to 3,000 shell per hour in a single line--evolved in studies by us in considerable detail--would be highly efficient, even though flexible to the extent of making projectiles and other bodies, both larger and smaller than the 30mm types, in both weight and size.

Frankford Arsenal

October, 1955

As to economics of the method, costs would be lower than any other current method, given recommended equipment and service requirement quantities, due in part to saving in metal.

Strategic saving of material--apparently not yet a major factor in choosing a method--will dictate cold forming beyond any question in any war economy.


Confirmed by a considerable exchange of actual visits it can be noted that European specialists in minor calibre cannon and ammunition have had excellent results from cold formed projectiles in late type weapons, that facilities in certain quarters there are quite limited in various respects as well as size; and that they not yet have access to the advanced technique described and suggested herein--although the interest is high.

The working organization here behind this and similar projects is being kept intact.

It is a pleasure to serve the Ordnance Corps.

Yours faithfully

HEINTZ MANUFACTURING COMPANY



Manager Ordnance Division

Weber deVore:eb



SUMMARY REPORT  
OF  
DEVELOPMENT, MANUFACTURE, AND METALLURGICAL STUDY  
OF THE  
PROJECTILE, PRACTICE, 30MM., T304  
PROJECTILE, PRACTICE, 30MM., T241  
PROJECTILE, TARGET PRACTICE, 30MM., T328  
SHELL, H.E.I., 30MM., T306E10  
ON  
Contract DA-36-038-ORD-14091



BY  
HEINTZ MANUFACTURING COMPANY  
PHILADELPHIA, PENNSYLVANIA


SEPTEMBER, 1955

PHOTOGRAPHS

Projectile, Practice, 30MM., T304.....	Frontispiece
Projectile, Practice, 30MM., T241.....	Frontispiece
Shell, H.E.I., 30MM., T306E10.....	Frontispiece
Projectile, Target Practice, 30MM., T328.....	Frontispiece









100-111121-100



100-111121-100



## CONTENTS

	<u>PAGE</u>
Preface.....	1
Summary.....	4
Conclusion.....	7
Technical Information.....	12
Projectile Practice, 30MM., T304 & T241	
Engineering Considerations .....	13
Cold Forming Operations .....	19
Machining and Finishing Operations.....	63
Inspection Gaging and Procedures.....	66
Metallurgical Data and Discussion .....	72
Shell, H.E.I., 30MM., T306F10	
Engineering Considerations .....	81
Cold Forming Operations .....	86
Machining and Finishing Operations.....	120
Metallurgical Data and Discussion .....	142
Projectile, Target Practice, 30MM., T328	
Engineering Considerations .....	146
Cold Forming Operations .....	150
Machining and Finishing Operations.....	178
Metallurgical Data and Discussion .....	207
Appendix.....	209

# DRAWINGS

<u>DWG. NO.</u>	<u>TITLE</u>	<u>PAGE</u>
B-122708	Projectile Practice T304.....	8
B-122769	Projectile Practice T241.....	9
FD-18083	Shell, H.E.I., T306E10.....	10
B-122715	Projectile, Target Practice, T328... ..	11
E-122716	Sequence of Operation on T241.....	17
E-122717	Sequence of Operation on T304.....	18
B-114782	Shearing Die T304 and T241.....	20
B-114782-1	Shearing Die T304 and T241.....	21
D-114782-2	Shear Clearance Template.....	22
B-114782-3	Shearing Die Detail T304 and T241... ..	23
B-114787	Sizing Die T241.....	30
D-114787-1	Punch and Bushing (Size) T241.....	31
D-114787-2	Modified Bushing (Size) T241.....	32
D-114787-3	Sizing Punch T241.....	33
D-114783	Sizing Die T241.....	34
D-114783-1	Punch and Bushing (Size) T304.....	35
D-114783-4	Punch (Size) T304.....	36
B-114788	Backward Extrusion Die T241.....	40
D-114788-1	Punch & Bushing T241 (Backward Extrusion)	41
B-114784	Final Backward Extrusion Die T304.....	42
D-114784-1	Punch and Bushing T304 (Final Backward Extrusion).....	43

# DRAWINGS

<u>DWG. NO.</u>	<u>TITLE</u>	<u>PAGE</u>
B-114789	Final Backward Extrusion Die T241.....	47
D-114789-1	Punch and Bushing and Knockout T241 Final Backward Extrusion).....	48
D-114789-2	Bushing (Final Backward Extrusion) T241.	49
B-114785	Final Backward Extrusion Die T304.....	50
B-114785-1	Shrink Ring Details T304 and T241.....	51
D-114785-2	Final Backward Extrusion Punch and Bushing T304. ....	52
B-114785-3	Lower Die Detail T304 and T241.....	53
B-114785-4	Punch Shoe Detail T304 and T241....	54
D-114785-6	Final Backward Extrusion Punch T304 ...	55
B-114790	Nosing Die T241.....	57
B-114790-1	Nosing Die Detail T241.....	58
D-114790-2	Die Part T241.....	59
B-114786	Nosing Die T304.....	60
D-114786-1	Die Detail (Nose) T304.....	61
SK-10290	Projectile Practice T241.....	65
B-115901	Concentricity Gage T304 and T241 ...	68
D-115902	Length Gage T241.....	69
D-115903	Length Gage T304.....	70
D-115904	Press Set Up Jig T304 and T241.....	71
	Hardness Survey.....	77

# DRAWINGS

<u>DWG. NO.</u>	<u>TITLE</u>	<u>PAGE</u>
	Hardness Pattern.....	79
	Hardness Pattern.....	80
E-120471	Sequence for Press Word on Body T306E10.	85
D-119843-1	Die Part Detail (Size) T306E10.....	93
B-119844	Backward Extrusion Die T328.....	97
D-119844-1	Die Part Detail (Backward Extrusion) T306E10.....	98
B-119845	Forward Extrusion Die T306E10 .....	102
D-119845-1	Forward Extrusion Die Part Detail T306E10	103
D-119845-2	Forward Extrusion Die Part Detail T306E10	104
D-119845-3	Forward Extrusion Die Part Detail T306E10	105
B-119846	Draw and Coin Die T306E10 .....	107
D-119846-1	Die Part Detail (Draw & Coin) T306E10. ...	108
B-119848	Nose Die T306E10 and T328.....	110
D-119848-1	Draw Die Punch T306E10.....	111
D-119848-2	Draw Die Part T306E10.....	112
E-119847-3	Die Part Details (Nose) T306E10.....	113
B-119847	Nose Die T306E10 and T328.....	115
D-119847-1	Die Part Detail (Nose) T306E10 .....	116
D-119847-2	Die Part Detail (Nose) T306E10.....	117
D-119847-3	Die Part Detail (Nose) T306E10.....	118
E-119836	Cold Formed Blank T306E10.....	121

## DRAWINGS

DWG. NO.	TITLE	PAGE
E-122730	Break Down Tools.....	123
D-122722	Tool Holder.....	124
E-122725	Finish Thread Relief.....	127
E-122731	Finish Band Groove - Tool.....	128
D-122720	Finish Groove and Face Tool Holder.....	129
E-122727	Break Down Tool.....	130
SK-10955	Layout of Turning 1/8 Rad. on Base T306E10.....	132
D-121117	Length Gage T306E10..... / .000	138
E-120474	Gage to check .965 - .006 Dia. T306E10.. / .020	139
E-120475	Gage to check .500 - .000 Dim. T306E10.	140
	Hardness Survey T306E10.....	144
	Tensile Test Specimen.....	145
E-120472	Press Sequence Layout Projectile T328...	149
B-119824	Size Die T328.....	156
D-119824-1	Die Part Detail T328.....	157
D-119824-2	Die Part Detail (Size) T328.....	158
D-119824-3	Die Part Detail (Size) T328.....	159
D-119824-4	Die Part Detail (Size) T328.....	160
D-119825-4	Die Part Detail (Pre-Backward Extrusion) T328.....	163
B-119825	First Backward Extrusion Die T328.....	166

# DRAWINGS

<u>DWG. NO.</u>	<u>TITLE</u>	<u>PAGE</u>
B-119825-1	Die Part Detail (Backward Extrusion) T328 .	167
B-119825-2	Die Part Detail (Backward Extrusion) T328 .	168
B-119825-3	Die Part Detail (Backward Extrusion) T328 .	169
B-119826	Second Backward Extrusion Die T328.....	172
B-119826-1	Die Part Detail (2nd B. E. ) T328.....	173
B-119826-2	Die Part Detail (2nd B. E. ) T328.....	174
B-119826-3	Die Part Detail (2nd B. E. ) T328.....	175
E-119837	Excess Metal on Shell Body T328.....	179
E-120473	Gage to Check .980 - .006 Dia. T328.....	183
SK-10954	Layout of Turning 1/8 Rad. on Base T328...	186
E-122724	Undercutting Tool.....	187
E-122726	Undercut Attachment Tool. ....	188
E-122728	Radius Tool.....	189
E-122729	3/4" Break Down Tool.....	190
E-122723	Form Tool.....	196
D-122721	Tool Post.....	197
E-120470	Gage to check .030 $\pm$ .009 Dim. Crimping Groove T306E10 & T328.....	204
D-121116	Length Gage T328.....	205
	Hardness Survey T328.....	208

## PREFACE

We are pleased to submit this summary report on the development, manufacture, and metallurgical study of the 30mm shell bodies as required by Contract DA-36-038-ORD-14091, as amended.

-----o-----

The original contract required in part that we "..... produce a complete set of tooling necessary to produce bodies, projectile, steel, 30mm, manufactured by extrusion from bar stock, stress relieved. Bodies shall conform to the following two types:

"a. Bodies conforming to ORD Dwg 7553344, Rev 2, dated 16 January 1953, except as modified with respect to the inside radii by Heintz Manufacturing Company Sketch Rev 16 February 1953.

"b. Bodies conforming to Sketch FSA 7757, Rev 7, dated 12 March, 1953, except as modified with respect to inside radii by Heintz Manufacturing Company Sketch Rev 16 February 1953."

And further, ".....the tooling to be delivered by the contractor shall be suitable for production of at least 50,000 each of these two bodies.

"A total of 5,000 of each of these two bodies produced

PREFACE (Cont.)

on the tooling designed for these bodies shall be delivered by the contractor f. o. b. Frankford Arsenal. A pilot lot of 25 to 100 each of these two bodies shall be delivered by the contractor f. o. b. Frankford Arsenal for approval prior to the production of the said 5,000 each of these two bodies."

-----o-----

Change Order No 1 (12 November 1953) provides  
".....pursuant to General Provisions, 2, Changes, of the contract, you are hereby authorized to incorporate in the base of the projectile the addition of a small flat indicated on sketch number 10290 dated 22 October 1953, of 9/16" diameter, which will join the rest of the spherical surface with no sharp edge or other deformation."

Change Order No 3 (16 March 1954) provides ".....  
you are hereby authorized to change the dimensions on the 30mm projectile T241, D-7553344 to 3.006 plus .000 minus .020 with no change in weight requirement, in lieu of 3.138 plus .000 minus .020."

Change Order No 4 (12 April 1954) states ".....you  
are hereby directed to change the two (2) types of Bodies for which tooling is to be delivered, to conform to the following types:

"Type 1: Body, Projectile, Practice, 30mm, T328,  
conforming to Dwg FD 18088, dated 26



PREFACE (Cont.)

February 1954.

"Type 2: Body, Shell, HEI, 30mm, T306E10, conforming to Dwg FD 18083, Rev 1 dated 17 February 1954.

"A pilot lot of fifty (50) to one hundred (100) each of these two (2) Bodies shall be delivered to Frankford Arsenal for approval; and production of 5,000 each of the two (2) Bodies shall be furnished after approval of the respective pilot lot."

Supplemental Agreement No 5 (1 December 1954) provides in part" . . . . the quantity of 5,000 each Bodies, Projectile, 30mm, T328 (Dwg FD 18088) shall be finish machined, banded, painted, and packaged in accordance with standard commercial practices to insure safe delivery to destination.

"The quantity of 5,000 each shell, projectile, 30mm, HEI, T306E10, (Dwg FD 18083) shall not be banded and shall be completely machined except for machining rotating band and the crimp groove. Shell bodies are not to be painted but are to be packaged in accordance with standard commercial practice to insure safe delivery to destination."

Supplemental Agreement No 6 (18 February 1955) provides for an extension of the delivery schedule.

## SUMMARY

This contract, as amended, required that four different 30mm shell bodies be produced by the methods of cold extrusion. They were the T241, T304, T328 and HEI T306E10.

The scope of this contract did not demand that the refinement of detail necessary for mass production be perfected. All of the work, therefore, comprising the cold forming phase of this project was performed using existing presses, surface treating equipment and annealing furnaces. This equipment was far too massive for these small shell. The presses employed were rated at tonnages greatly in excess of that required and the strokes they made per minute were correspondingly few. The surface treating equipment was equally ill-suited. It was necessary to fabricate temporary containers in an effort to utilize the present equipment with some detrimental effect on the quality of the phosphate coating. The shell were annealed in large electrically energized batch type furnaces.

The use of this heavy equipment in no way detracted from the development of the essential mechanical, chemical and metallurgical principles which are applicable to production. Listed in the Appendix are suggestions concerning the equipment necessary for economical mass production of these shell.

## SUMMARY (Cont.)

The first portion of the cold forming phase of this project was to determine the sequence of press operations, anneals and surface treatment that would produce not only a dimensionally correct shell but also a shell which had been plastically formed to just the proper degree to impart the required mechanical properties. The variety of shapes found among these four shell required three distinct approaches. Therefore, the description of the manufacturing operations will be divided into three parts. The first will include the bodies T241 and T304, which were similar in nature in that both were made with the following basic sequence of press operations:

1. Shear
2. Size
3. First Backward Extrude
4. Second Backward Extrude
5. Nose

The T328 body was produced using a similar basic sequence but the flat bottom and deep backward extrusion imposed a different set of problems.

The HEI T306E10 shell body was manufactured using an entirely different type of operations which were fundamentally:

1. Shear
2. Size
3. Backward Extrude
4. Forward Extrude
5. Draw & Coin
6. Nose

## SUMMARY (Cont.)

The press operations produced all of these shell with the internal and external contour finished with the exception of the threads and the band groove and crimping groove.

All of the machining equipment available at Heintz Manufacturing Company was suitable only for much larger work. It was necessary, therefore, to subcontract.

The machining of bodies T241 and T304 was subcontracted to G M Co. Mfg., Inc., of Long Island City, New York, while the bodies T328 and HEI T306E10 were sent to Pantex, Inc., of Pawtucket, Rhode Island. Both of these companies had machined 30mm shell from bar stock using automatic screw machines, and had the necessary form tools, rotating bands, inspection gages, jigs and fixtures, etc., for these shell.

The machining of the nose end of the shell body consisted of facing to length and boring and tapping the thread. With the shell reversed, the band seat was formed and knurled, the band applied and formed and the crimping groove machined.

The shell were then finished and packed as required.

Government inspection and testing were done at Frankford Arsenal.

## CONCLUSIONS

This development project clearly demonstrates the practicality and advisability of using the methods of cold extrusion to fabricate small caliber ammunition of this type.


(Although the scope of this contract did not include the economic aspects of the method of manufacture, a casual study of this and other methods indicates clearly that both strategically and economically high production of such items by the methods used would have considerable advantage. Easily obtainable high speed equipment can produce these shell at a saving in material (both quantity and quality) and in cost.)

Cold extrusion, with its relative ease of precision duplication, converts hot rolled bar stock into a finished piece with superior finish and requiring only the minimum of machining. The required mechanical properties are imparted to the shell as an inherent part of the process eliminating entirely the necessity of quench hardening and tempering.

The tooling is readily adaptable to high speed presses and automatic feeding devices.



STANDARD DRAWING



ATTACHED TO DETAIL A-1  
A PART NUMBER OF DRAWING



DETAIL OF ROTATING BAND  
SCALE 1/2"

SEE DETAIL A-1  
A PART NUMBER OF DRAWING

SEE DETAIL A-1  
A PART NUMBER OF DRAWING

SEE DETAIL A-1  
A PART NUMBER OF DRAWING

SEE DETAIL A-1  
A PART NUMBER OF DRAWING

SEE DETAIL A-1  
A PART NUMBER OF DRAWING

SEE DETAIL A-1  
A PART NUMBER OF DRAWING

SEE DETAIL A-1  
A PART NUMBER OF DRAWING

SEE DETAIL A-1  
A PART NUMBER OF DRAWING

SEE DETAIL A-1  
A PART NUMBER OF DRAWING

SEE DETAIL A-1  
A PART NUMBER OF DRAWING

SEE DETAIL A-1  
A PART NUMBER OF DRAWING

SEE DETAIL A-1  
A PART NUMBER OF DRAWING

SEE DETAIL A-1  
A PART NUMBER OF DRAWING

SEE DETAIL A-1  
A PART NUMBER OF DRAWING

SEE DETAIL A-1  
A PART NUMBER OF DRAWING

SEE DETAIL A-1  
A PART NUMBER OF DRAWING

SEE DETAIL A-1  
A PART NUMBER OF DRAWING

BODY

REFER TO STANDARD DRAWING D755344  
DATED OCTOBER 1965

D755344 - PROJECT  
HENTZ MFG CO. PART 1000000000

B-122700

FILE NO. CHANGES

DATE

BY

REVISION

DESCRIPTION

DATE


BY

REVISION

DESCRIPTION

DATE

**NOTE**  
● FOR INFORMATIONAL PURPOSES ONLY




**VIEW OF ROTATING BAND  
AND CRIMPING GROOVE**

**NOTE**  
• **COMPOSITION**

ELEMENT	PERCENT
COPPER	0.00 - 0.00
TIN	0.00 - 0.00
SILICON	0.15 - 0.25
BARBARINE	0.05 - 0.10
• ZINC	0.05 - 0.10
• PHOSPHORUS	0.05 - 0.10
• LITHIUM	0.05 - 0.10
• ALUMINUM	0.05 - 0.10
• IRON	0.05 - 0.10

TOTAL IMPURITIES INCLUDES  
THOSE MARKED • NOT TO  
EXCEED 0.05%




SECTION 0-0



COVER BASE F010003C

COVER, BASE  
STEEL-WIDIO TO WIDIO  
SPEC 57-136  
TEMPER NO 4, FINISH NO 1  
WEIGHT 30 GRAMS APPROX



**BODY, ASSEMBLY**  
HARDEN TO ROCKWELL C40-45  
SCALE - 1


NOTICE -  
THIS SERVICE SHALL NOT BE USED FOR  
SUSPENDED ITEMS ONLY OR IN PART  
EXCEPT WHEN APPROVED IN WRITING  
BY THE STATES GOVERNMENT AND  
COMPANY

1. FOR TOLERANCE STUDY INTERPRETATION SEE DRAWING 30-1-7
2. EXTERIOR SURFACES OF BELL SHALL BE SMOOTH AND FREE FROM ANY SCALING, PITS, ETC.
3. REMOVE ALL BURRS
4. STAMP COMBINATIONS OF ROTATING BAND WITH 4 LETTERS AND  
 - NUMBER, LOT NUMBER, YEAR OF MANUFACTURE, CALIBER AND  
 ORIGINATION OF BELL.
5. THE 1/16" - .005 GORRELLY DIAMETER MAY BE REDUCED BY  
 SMOOTH CONTINUOUS TAPER TO 1/64 MIN DIAMETER AT FORWARD  
 END OF EACH ATTACHING STUD.

NOTICE -  
THIS SERVICE SHALL NOT BE USED FOR  
SUSPENDED ITEMS ONLY OR IN PART  
EXCEPT WHEN APPROVED IN WRITING  
BY THE STATES GOVERNMENT AND  
COMPANY

[illegible]





## TECHNICAL INFORMATION

The sequence of manufacturing operations listed and described hereafter was used to make pilot lots and production runs up to 5,000 pieces. While this represents a small total number of shell produced, the principles, the methods, and the tools are analogous to those used to make similar, if larger, components on a mass production basis.

The several basically different approaches that were necessary to make these four shell require that each approach be described separately. Therefore the work described hereafter will be presented as follows:

### 1. Shell Designation

- a. Engineering Considerations
- b. Cold Forming Operations and Applicable Tool Drawings
- c. Machining Operations and Applicable Drawings
- d. Metallurgical Data and Discussion

BODY, PROJECTILE, PRACTICE, 30MM

T304 and T241

## BODY, PROJECTILE, PRACTICE, 30MM

T304 and T241

### ENGINEERING CONSIDERATIONS

These two shell were so similar with respect to physical shape and mechanical properties that this discussion of the engineering problems is applicable to both.

The general requirement was to manufacture a shell dimensionally consistent with the required drawings and having a minimum yield strength of 90,000 psi with an elongation of 10% in a gage length of four (4) diameters. The mechanical properties were to be derived from work hardening the material.

To assure that these requirements were met a sequence of operations compatible with the requirements of both shape and mechanical properties had to be properly determined. The general method of approach is to engineer the sequence with respect to shape and dimensional requirements only and then select a material which will, at the calculated strain, have approximately the mechanical properties desired. Then the sequence, material, process anneals and final stress relief anneal are modified to give the desired result.

In the particular case of these two shell bodies, which had been designed for production on automatic screw machines, it was first necessary to modify the sharp corners in the cavity with radii. This was essential in that the material flowing from under the punch

## BODY, PROJECTILE, PRACTICE, 30MM

T304 and T241

### ENGINEERING CONSIDERATIONS (Cont.)

did not have sufficient ductility to form around the sharp edges and would rupture. Also such sharp corners had a deleterious effect on the lubricating properties of the phosphate coating.

The cavity and general shape of these bodies lent themselves admirably to forming by successive backward extrusion operations followed by nosing to form the ogive. The difference in internal diameters, with a constant outside diameter, resulted in a 65% reduction in area at the top of the shell and a 27% reduction in area at the bottom in the extreme case of the T241 body. The smaller reduction therefore governed the extent of the work hardening. A reduction in area of 27% should increase the "as rolled" yield point approximately 85% and decrease the elongation by approximately 55%. Therefore, a steel with yield strength of approximately 50,000 psi and an elongation of 36% in the "as rolled" condition should be selected. A plain carbon steel with about 20 points of carbon meets these conditions.

Since the sequence of operations selected with a series of backward extrusions, where the metal worked by the first backward extrusion was not further strained by the second backward extrusion. This, of course, precluded the use of any anneals following the first extrusion.

## BODY, PROJECTILE, PRACTICE, 30MM

T304 and T241

### ENGINEERING CONSIDERATIONS (Cont.)

Economic considerations made it mandatory that the billets be sheared from the bars rather than sawed. This shearing operation produced a distorted slug of metal with a very irregular and severely cold worked top and bottom face. To prepare this slug for the first backward extrusion operation, it was necessary to tumble to remove burrs and sharp edges, then to anneal to remove the effects of the shearing, and finally to add another press operation to size this deformed slug into a cylindrical section. If the billets were not sized, the skewed surface of the sheared billet would have caused the punch to enter the piece at an angle and would have made it impossible to hold the shell bodies within the required concentricity tolerances.

Previous experience had indicated that conical punch shapes, as required to form these shell, impose some limitations on the extent to which the phosphate coating may be stretched when forming the metal. This type of punch is not as desirable as one with a flat or hemispherical shape. Experimental work confirmed this thinking and the pieces were surface treated preceding each of the backward extrusion operations as well as after the annealing operation.

With these considerations in mind the necessary volumetric

## BODY, PROJECTILE, PRACTICE, 30MM

T304 and T241

### ENGINEERING CONSIDERATIONS (Cont.)

calculations were made and the sequence drawings shown on the pages immediately following this text were prepared.

The complete theoretical or basic sequence of cold forming operations was therefore:

1. Shear billet
2. Tumble
3. Anneal
4. Wheelabrator
5. Surface treat
6. Size
7. Surface treat
8. First backward extrusion
9. Surface treat
10. Second backward extrusion
11. Nose
12. Stress relieve

Once this information was determined, tools were designed and built to make the shapes shown on the sequence drawings, tentative annealing temperatures were selected, required press tonnages were calculated, the auxiliary equipment necessary for surface treatment was fabricated, and the necessary gages, jigs and fixtures were manufactured.

These operations will now be discussed in detail with regard to the practical tooling, metallurgical, chemical and manufacturing problems.

## BODY, PROJECTILE, PRACTICE, 30MM

T304 and T241

### ENGINEERING CONSIDERATIONS (Cont.)

calculations were made and the sequence drawings shown on the pages immediately following this text were prepared.

The complete theoretical or basic sequence of cold forming operations was therefore:

1. Shear billet
2. Tumble
3. Anneal
4. Wheelabrator
5. Surface treat
6. Size
7. Surface treat
8. First backward extrusion
9. Surface treat
10. Second backward extrusion
11. Nose
12. Stress relieve

Once this information was determined, tools were designed and built to make the shapes shown on the sequence drawings, tentative annealing temperatures were selected, required press tonnage was calculated, the auxiliary equipment necessary for surface treatment was fabricated, and the necessary gages, jigs and fixtures were manufactured.

These operations will now be discussed in detail with regard to the practical tooling, metallurgical, chemical and manufacturing problems.





A		F		E		K		J. H. WOOD & CO., PHILA.	
B		G		F		J			
C		H		G		K			
D		I		H		L			
E		J		I		M			
		K		J		N			
		L		K		O			
		M		L		P			
		N		M		Q			
		O		N		R			
		P		O		S			
		Q		P		T			
		R		Q		U			
		S		R		V			
		T		S		W			
		U		T		X			
		V		U		Y			
		W		V		Z			
		X		W		AA			
		Y		X		AB			
		Z		Y		AC			
		AA		Z		AD			
		AB		AA		AE			
		AC		AB		AF			
		AD		AC		AG			
		AE		AD		AH			
		AF		AE		AI			
		AG		AF		AJ			
		AH		AG		AK			
		AI		AH		AL			
		AJ		AI		AM			
		AK		AJ		AN			
		AL		AK		AO			
		AM		AL		AP			
		AN		AM		AQ			
		AO		AN		AR			
		AP		AO		AS			
		AQ		AP		AT			
		AR		AQ		AU			
		AS		AR		AV			
		AT		AS		AW			
		AU		AT		AX			
		AV		AU		AY			
		AW		AV		AZ			
		AX		AW		BA			
		AY		AX		BB			
		AZ		AY		BC			
		BA		AZ		BD			
		BB		BA		BE			
		BC		BB		BF			
		BD		BC		BG			
		BE		BD		BH			
		BF		BE		BI			
		BG		BF		BJ			
		BH		BG		BK			
		BI		BH		BL			
		BJ		BI		BM			
		BK		BJ		BN			
		BL		BK		BO			
		BM		BL		BP			
		BN		BM		BQ			
		BO		BN		BR			
		BP		BO		BS			
		BQ		BP		BT			
		BR		BQ		BU			
		BS		BR		BV			
		BT		BS		BW			
		BU		BT		BX			
		BV		BU		BY			
		BW		BV		BZ			
		BX		BW		CA			
		BY		BX		CB			
		BZ		BY		CC			
		CA		BZ		CD			
		CB		CA		CE			
		CC		CB		CF			
		CD		CC		CG			
		CE		CD		CH			
		CF		CE		CI			
		CG		CF		CJ			
		CH		CG		CK			
		CI		CH		CL			
		CJ		CI		CM			
		CK		CJ		CN			
		CL		CK		CO			
		CM		CL		CP			
		CN		CM		CQ			
		CO		CN		CR			
		CP		CO		CS			
		CQ		CP		CT			
		CR		CQ		CU			
		CS		CR		CV			
		CT		CS		CW			
		CU		CT		CX			
		CV		CU		CY			
		CW		CV		CZ			
		CX		CW		DA			
		CY		CX		DB			
		CZ		CY		DC			
		DA		CZ		DD			
		DB		DA		DE			
		DC		DB		DF			
		DD		DC		DG			
		DE		DD		DH			
		DF		DE		DI			
		DG		DF		DJ			
		DH		DG		DK			
		DI		DH		DL			
		DJ		DI		DM			
		DK		DJ		DN			
		DL		DK		DO			
		DM		DL		DP			
		DN		DM		DQ			
		DO		DN		DR			
		DP		DO		DS			
		DQ		DP		DT			
		DR		DQ		DU			
		DS		DR		DV			
		DT		DS		DW			
		DU		DT		DX			
		DV		DU		DY			
		DW		DV		DZ			
		DX		DW		EA			
		DY		DX		EB			
		DZ		DY		EC			
		EA		DZ		ED			
		EB		EA		EE			
		EC		EB		EF			
		ED		EC		EG			
		EE		ED		EH			
		EF		EE		EI			
		EG		EF		EJ			
		EH		EG		EK			
		EI		EH		EL			
		EJ		EI		EM			
		EK		EJ		EN			
		EL		EK		EO			
		EM		EL		EP			
		EN		EM		EQ			
		EO		EN		ER			
		EP		EO		ES			
		EQ		EP		ET			
		ER		EQ		EU			
		ES		ER		EV			
		ET		ES		EW			
		EU		ET		EX			
		EV		EU		EY			
		EW		EV		EZ			
		EX		EW		FA			
		EY		EX		FB			
		EZ		EY		FC			
		FA		EZ		FD			
		FB		FA		FE			
		FC		FB		FF			
		FD		FC		FG			
		FE		FD		FH			
		FF		FE		FI			
		FG		FF		FJ			
		FH		FG		FK			
		FI		FH		FL			
		FJ		FI		FM			
		FK		FJ		FN			
		FL		FK		FO			
		FM		FL		FP			
		FN		FM		FQ			
		FO		FN		FR			
		FP		FO		FS			
		FQ		FP		FT			
		FR		FQ		FU			
		FS		FR		FV			
		FT		FS		FW			
		FU		FT		FX			
		FV		FU		FY			
		FW		FV		FZ			
		FX		FW		GA			
		FY		FX		GB			
		FZ		FY		GC			
		GA		FZ		GD			
		GB		GA		GE			
		GC		GB		GF			
		GD		GC		GG			
		GE		GD		GH			
		GF		GE		GI			
		GG		GF		GJ			
		GH		GG		GK			
		GI		GH		GL			
		GJ		GI		GM			
		GK		GJ		GN			
		GL		GK		GO			
		GM		GL		GP			
		GN		GM		GQ			
		GO		GN		GR			
		GP		GO		GS			
		GQ		GP		GT			
		GR		GQ		GU			
		GS		GR		GV			
		GT		GS		GW			
		GU		GT		GX			
		GV		GU		GY			
		GW		GV		GZ			
		GX		GW		HA			
		GY		GX		HB			
		GZ		GY		HC			
		HA		GZ		HD			
		HB		HA		HE			
		HC		HB		HF			
		HD		HC		HG			
		HE		HD		HH			
		HF		HE		HI			
		HG		HF		HJ			
		HH		HG		HK			
		HI		HH		HL			
		HJ		HI		HM			
		HK		HJ		HN			
		HL		HK		HO			
		HM		HL		HP			
		HN		HM		HQ			
		HO		HN		HR			
		HP		HO		HS			
		HQ		HP		HT			
		HR		HQ		HU			
		HS		HR		HV			
		HT		HS		HW			
		HU		HT		HX			
		HV		HU		HY			
		HW		HV		HZ			
		HX		HW		IA			
		HY		HX		IB			
		HZ		HY		IC			
		IA		HZ		ID			
		IB		IA		IE			
		IC		IB					

## BODY, PROJECTILE, PRACTICE, 30MM

T304 and T241

### COLD FORMING OPERATIONS


#### 1. SHEAR BILLETS

The billets were sheared to the correct weight of nine (9) ounces for the T241 and seven and one-half (7-1/2) ounces for the T304 from one and one-quarter inch (1.250") hot rolled AISI 1021 bar stock. The random length bars were hand fed into the die against the stop block on the upstroke of the press.


Little difficulty was experienced in performing this operation with the exception of the troublesome accumulation of galled metal from the bar stock which tended to deposit on the stop block. An improved die designed for one particular shell only would allow for a removable block.

The assembly drawing and details of this die appear on the pages immediately following this text.

This die was run on a Verson 100 ton mechanical press. The actual tonnage required was 43 tons.







SCALE = 10 x SIZE

[illegible]



BODY, PROJECTILE, PRACTICE, 30MM

T304 and T241

COLD FORMING OPERATIONS (Cont.)

2. TUMBLE BILLETS

The purpose of tumbling was to remove the sharp edges and burrs from the faces of the billet.

This was an economical operation in that it only required a part-time operator to load and unload the tumbler, and in the cycle of forty-five (45) minutes, one thousand (1,000) pieces could be processed.



## BODY, PROJECTILE, PRACTICE, 30MM

T304 and T241

### COLD FORMING OPERATIONS (Cont.)

#### 3. ANNEAL BILLETS

The sheared surface of the billet was, of course, cold worked to its breaking point. This surface was then incapable of withstanding any further plastic deformation unless it was annealed at a temperature that would restore its original ductility.

The pieces were heated to 1250° F. in an electric furnace, manufactured by the Lindberg Engineering Company, soaked at this temperature for three-quarters of an hour and air cooled. The effect of this anneal is shown, by means of hardness surveys, in the section on metallurgical information.

## BODY, PROJECTILE, PRACTICE, 30MM

T304 and T241

### COLD FORMING OPERATIONS (Cont.)

#### 4. SHOTBLAST BILLETS

All production procedures for cold forming utilize some form of automatic surface treating equipment. With this automatic equipment it is impossible to have a chemical cycle that is compatible with the scaled surface of the billets and the surface of pieces that have been partially formed. Mechanical "Wheelabrating" is the most economical method of removing this tenacious scale.

The pieces were placed on a conveyor which fed them into the machine. They were ejected from the machine automatically by a conveyor which led away from the machine and dropped the pieces into an empty bin.

Soft "nail whiskers" were used for shot. It was very important to have soft shot of some form in that hard shot would imbed itself in the relatively soft piece and then gouge the die when the piece was formed.

BODY, PROJECTILE, PRACTICE, 30MM

T304 and T241

COLD FORMING OPERATIONS (Cont.)

5. SURFACE TREAT BILLETS

The surface treatment of billets was performed on the experimental, hand Foscoat line. The pieces were placed in stainless steel (Carpenter #20) trays which we used to modify the existing baskets. The process was as follows:

1. Alkaline clean
2. Cold water rinse
3. Sulphuric acid pickle
4. Cold, overflowing water rinse
5. Hot, overflowing water rinse
6. Foscoat
7. Cold, overflowing water rinse
8. Hot, overflowing water rinse
9. Lubrication

Chemicals were furnished by Pennsylvania Salt Manufacturing Company of Philadelphia.

A complete description of the processes and controls is contained in the Appendix section describing chemical data.

## BODY, PROJECTILE, PRACTICE, 30MM

T304 and T241

### COLD FORMING OPERATIONS (Cont.)

#### 6. SIZE BILLETS

The tools necessary to perform this operation are shown on Dwg #114783 and #114787 on the pages immediately following this text. The punch (item #7), the die (item #8), and the knock-out pin (item #18), were those components which actually formed the piece. The remainder of the die assembly was designed to accommodate not only this operation but all extrusion operations.

The Foscoated one and one-quarter inch (1-1/4") billet was placed in the die and formed approximately to the shape shown on Dwg #122717 and #122716. Actually, the punch forced the metal to form into the spherical bottom until the vertical forces were balanced; i.e., until a stress level was reached where the metal would flow up around the punch rather than into the die. Considerable difficulty of this nature was experienced and in an effort to form a perfect hemisphere, the punch and die were modified as shown on Dwg #D-114783-1, #D-114783-4, #D-114787-1 and #D-114787-3. These modifications markedly improved the flow problem but were not completely successful in forcing the metal to conform to the


BODY, PROJECTILE, PRACTICE, 30MM

T304 and T241


COLD FORMING OPERATIONS (Cont.)

SIZE BILLETS (Cont.)

hemispherical shape. This die was run on a Verson 100 ton single point mechanical press. Actual tonnage required was 159 tons for the T241 and 105 tons for the T304.



2.000  
1.500



OBSOLETE  
SEE DRAWING  
D-114787-2

OBSOLETE  
SEE DRAWING  
D-114787-2

HEINTZ MFG. CO.  
PHILADELPHIA, PA.  
DRAWN: [blank] CHECKED: [blank]  
DATE: [blank] DATE: [blank]

PRICE: \$1.00  
QTY: 100  
MATERIAL: 304 STAINLESS STEEL  
FINISH: POLISHED

D-114787-2  
2.000

HEINTZ MFG. CO.  
PHILADELPHIA, PA.  
DRAWN: [blank] CHECKED: [blank]  
DATE: [blank] DATE: [blank]

PRICE: \$1.00  
QTY: 100  
MATERIAL: 304 STAINLESS STEEL  
FINISH: POLISHED


D-114787-2  
2.000

HEINTZ MFG. CO.  
PHILADELPHIA, PA.  
DRAWN: [blank] CHECKED: [blank]  
DATE: [blank] DATE: [blank]

PRICE: \$1.00  
QTY: 100  
MATERIAL: 304 STAINLESS STEEL  
FINISH: POLISHED

D-114787-2  
2.000

OBsolete PUNCH  
SEE DRAWING  
D-114787-3



5145-000 DA


A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V										
																						HEINTZ MFG CO. PHILADELPHIA, PA.		DRAWN		CHECKED		APPROVED		DATE	
																						D-									
																						FILE NO.		CHANGE							
																						ADDRESS, USE OR UNIT									
																						CART NO.									
																						METAL									
																						NO. 1000									











A		F	J	R	
B		G	K	S	
C		H	L	T	
D		I	M	U	
E		J	N	V	

HEINTZ MFG. CO. PHILADELPHIA, PA.	BUNCH	30MM T304 50" PL 7757	5"Z
10-18-83	10-18-83	REINFORCED ARRAVAL PUNA	DRUM

23701  
DIE NO  
D-114783-4

[illegible]

BODY, PROJECTILE, PRACTICE, 30MM

T304 and T241

COLD FORMING OPERATIONS (Cont.)

7. SURFACE TREAT SIZED PIECE

This operation was identical with Operation #5.

This surface treatment was eliminated on a test group of pieces, but the results indicated that the residual Foscoat on the sized pieces was not sufficient to withstand the first backward extrusion operation.

## BODY, PROJECTILE, PRACTICE, 30MM

T304 and T241

### COLD FORMING OPERATIONS (Cont.)

#### 8. FIRST BACKWARD EXTRUSION

The complete tooling required to perform this operation is shown on Dwg #114784 and #114788 on the pages immediately following this text.

This die formed the .945" inside diameter of the shell bodies. The Foscoated sized piece was placed in the die and the punch forced the piece down further into the die until a stress level was reached in the piece which balanced the vertical loads. Then the metal under the punch flowed upward through the annular orifice between punch and die.

Considerable care had to be exercised in aligning this die and the variation in wall thickness of the extruded piece had to be checked to assure that it was within the allowable tolerance.


This piece should form the cavity with the desired shape as shown on Dwg #122717 and #122716.

Considerable trouble in this respect was experienced with both shell bodies in that the piece still did not fill out the hemispherical cavity of the die. This made it extremely difficult to measure the metal remaining in the unextruded section. This difficulty



+000  
-20003

1 1/2  
1 1/2  
1 1/2



+000  
-100  
1275

+000  
-100  
1275



+000  
-100  
1275

BUSHING

MATERIAL - STAINLESS STEEL  
HARDEN R. 54 5% & 1/2

A	FILE NO.	CHANGE	NO. 114500	DATE 4-20-55	BY 37876
B	FILE NO.	CHANGE	NO. 114500	DATE 4-20-55	BY 37876
C	FILE NO.	CHANGE	NO. 114500	DATE 4-20-55	BY 37876
D	FILE NO.	CHANGE	NO. 114500	DATE 4-20-55	BY 37876
E	FILE NO.	CHANGE	NO. 114500	DATE 4-20-55	BY 37876

HEINTZ MFG CO	PHILADELPHIA PA	HEINTZ MFG CO (B.E.)	30 MIN. T261	QUG No. 755344
HEINTZ MFG CO	PHILADELPHIA PA	HEINTZ MFG CO (B.E.)	30 MIN. T261	QUG No. 755344
HEINTZ MFG CO	PHILADELPHIA PA	HEINTZ MFG CO (B.E.)	30 MIN. T261	QUG No. 755344
HEINTZ MFG CO	PHILADELPHIA PA	HEINTZ MFG CO (B.E.)	30 MIN. T261	QUG No. 755344
HEINTZ MFG CO	PHILADELPHIA PA	HEINTZ MFG CO (B.E.)	30 MIN. T261	QUG No. 755344







## BODY, PROJECTILE, PRACTICE, 30MM

T304 and T241

### COLD FORMING OPERATIONS (Cont.)

#### 9. SURFACE TREAT

The chemical aspects of this operation were identical with Operation #5.

However, the deep impression formed by backward extrusion tended to air lock when the pieces were being treated unless provision was made to rack the pieces in a manner that would allow the air to escape from the cavity as the particular solution entered it.

In actual practice this was accomplished by placing the pieces in baskets that were designed to rotate about 30° on either side of the level position.

## BODY, PROJECTILE, PRACTICE, 30MM

T304 and T241

### COLD FORMING OPERATIONS (Cont.)

#### 10. FINAL BACKWARD EXTRUSION

This operation is similar in principle for both shell but differed in both depth and severity from the thin bottom .770" diameter T304 body to the thick bottom 5/8" diameter T241 body. The results, for this reason, differed considerably.

The force required to form the .770" inside diameter of the T304 shell, coupled with the extreme depth of penetration of the punch, forced the metal to fill completely the lower die cavity. The lighter vertical load generated when forming the 5/8" inside diameter of the T241 shell was not sufficient to cause the metal to flow completely into the cavity. This was the reason for the deviation which allowed a 9/16" diameter flat to be machined across the otherwise hemispherical surface of the T241 body.

The tools to perform this operation are shown on Dwg #B-114785 and #B-114789.

A 100 ton mechanical single point Clearing Machine Corporation press was used. The actual tonnages required were 67 tons for the T304 shell and 46 tons for the T241 shell.

Reference to the sequence Dwg #E-112717 and #E-112716

## BODY, PROJECTILE, PRACTICE, 30MM


T304 and T241

### COLD FORMING OPERATIONS (Cont.)

#### FINAL BACKWARD EXTRUSION (Cont.)

indicates if the bottom thickness in the first backward extrusion was not held within extremely close tolerances, either too much or too little metal would have been displaced by the punch during the second backward extrusion. This would have varied the position of the shoulder in the cavities of the bodies more than the allowable tolerance. Since there was considerable variation in the degree to which the metal filled the hemispherical die cavity during the first backward extrusion, it was at first impossible to maintain the position of the shoulder.


This problem was solved by making a final backward extrusion punch as shown on Dwg #D-114789-2 and forming not only the small lower inside diameter of the shell in this operation, but also a portion of the larger upper inside diameter. In this manner the position of the shoulder was accurately controlled.
















[illegible]



1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100	101	102	103	104	105	106	107	108	109	110	111	112	113	114	115	116	117	118	119	120	121	122	123	124	125	126	127	128	129	130	131	132	133	134	135	136	137	138	139	140	141	142	143	144	145	146	147	148	149	150	151	152	153	154	155	156	157	158	159	160	161	162	163	164	165	166	167	168	169	170	171	172	173	174	175	176	177	178	179	180	181	182	183	184	185	186	187	188	189	190	191	192	193	194	195	196	197	198	199	200	201	202	203	204	205	206	207	208	209	210	211	212	213	214	215	216	217	218	219	220	221	222	223	224	225	226	227	228	229	230	231	232	233	234	235	236	237	238	239	240	241	242	243	244	245	246	247	248	249	250	251	252	253	254	255	256	257	258	259	260	261	262	263	264	265	266	267	268	269	270	271	272	273	274	275	276	277	278	279	280	281	282	283	284	285	286	287	288	289	290	291	292	293	294	295	296	297	298	299	300	301	302	303	304	305	306	307	308	309	310	311	312	313	314	315	316	317	318	319	320	321	322	323	324	325	326	327	328	329	330	331	332	333	334	335	336	337	338	339	340	341	342	343	344	345	346	347	348	349	350	351	352	353	354	355	356	357	358	359	360	361	362	363	364	365	366	367	368	369	370	371	372	373	374	375	376	377	378	379	380	381	382	383	384	385	386	387	388	389	390	391	392	393	394	395	396	397	398	399	400	401	402	403	404	405	406	407	408	409	410	411	412	413	414	415	416	417	418	419	420	421	422	423	424	425	426	427	428	429	430	431	432	433	434	435	436	437	438	439	440	441	442	443	444	445	446	447	448	449	450	451	452	453	454	455	456	457	458	459	460	461	462	463	464	465	466	467	468	469	470	471	472	473	474	475	476	477	478	479	480	481	482	483	484	485	486	487	488	489	490	491	492	493	494	495	496	497	498	499	500	501	502	503	504	505	506	507	508	509	510	511	512	513	514	515	516	517	518	519	520	521	522	523	524	5
---	---	---	---	---	---	---	---	---	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	---



WRENCH FOR NUT (ASSEM & DETAILS)  
WRENCH - 10 Double Flats (2 Rows)  
CRS  
CRS

Section A-A

19 20

2

$P_{\text{max}} = 2.4 \text{ W}$

2010-01-01

DOUGH RETAINER  
-MATERIAL- CIRS

Math 11

[illegible]

B-114785-4  
Doc No. 23703

MEINTE MFG. CO. P.O. BOX 100 MILWAUKEE, WIS.	DATE OF ORDER JAN 1968	QUANTITY 24.83	PRICE \$1.12	TOTAL \$27.50
--	---------------------------	-------------------	-----------------	------------------

[illegible][illegible]

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100
---	---	---	---	---	---	---	---	---	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	-----

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100
---	---	---	---	---	---	---	---	---	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	-----

[illegible]

4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100
---	---	---	---	---	---	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	-----



## BODY, PROJECTILE, PRACTICE, 30MM

T304 and T241

### COLD FORMING OPERATIONS (Cont.)


#### 11. NOSING

The previous press operation worked only the base portion of the shell leaving the Foscoat on the open end undisturbed. Therefore, no further lubrication was needed to perform this operation.

The final backward extruded piece was placed in the die with its open end down. A hemispherically concave punch forced the shell into the die which formed the nose shape and sized the outside diameter.

The tools necessary to perform this operation are shown on Dwg #114786 and #114790.

The die was run on a 100 ton Clearing Machine Corporation single point press. The actual force required was approximately ten tons.



# THE

PARTS - 10 1 2 3 4 5 & 6 ARE NOT TO BE USED  
FOR THIS USE

[illegible][illegible]

114500	114500
4000-13	4000-13
302	302
37030	37030
B-114790	B-114790
23708	23708


<b>MINTZ MFG. CO.</b>	Sales Div	DIC	Order No. 758964
INDUSTRIAL PARK, INC.	30 Apr '74	Export Field	Price \$

[illegible]











# BODY, PROJECTILE, PRACTICE, 30MM

T304 and T241

## COLD FORMING OPERATIONS (Cont.)

### 12. STRESS RELIEF

The finished shell were placed in a Lindberg Electric Furnace, heated to a temperature of 740° F., held at this temperature for one (1) hour and air cooled.

The experimental work which was done to determine this temperature as well as the theoretical considerations involved will be discussed in more detail in the section on metallurgical data.

## BODY, PROJECTILE, PRACTICE, 30MM

T304 and T241

### MACHINING AND FINISHING OPERATIONS

Since only a very small quantity of these two shell (less than one hundred (100) each) were manufactured, the machining and allied operations, which were performed on turret lathes, will be described only in very general terms.

The machining operations necessary to finish a cold shell will be described in detail in conjunction with the description of manufacture of shell bodies T328 and T306E10 which follows. These shell we produced in quantities large enough to warrant using automatic machinery.

The first operation, which was done in a turret lathe, faced the open end to length, bored and chamfered the mouth diameter and tapped the 1-20 UNEF-2B thread.

With the piece chucked at the open end, the second operation formed and knurled the band seat.

The rotating bands were applied using a small mechanical press. Each band was given two squeezes, at right angles to one another, to seat it in the groove and around the knurls.

The third and final lathe operation rough turned and

## BODY, PROJECTILE, PRACTICE, 30MM

T304 and T241

### MACHINING AND FINISHING OPERATIONS (Cont.)

finish formed the rotating band and also formed the crimping groove.

The 9/16" diameter flat was machined on the base of the T241 shell body as a part of this operation and as shown by SK 10920 which is found on the following page.

The final operations necessary to complete the shell such as stencilling, bonderizing, painting, etc., were performed. A detailed description of such operations and the automatic equipment used will be discussed in conjunction with shell T328 and T306E10.





## BODY, PROJECTILE, PRACTICE, 30MM

T304 and T241

### INSPECTION GAGING AND PROCEDURES

The small number of shell produced prohibited either purchasing or building the quantity of gages that would be required for mass production.

The final inspection gages were the required standard gages of the snap, ring, plug and thread variety and were the property of the subcontractor.

Gages designed and built by the Heintz Manufacturing Company for checking the cold forming operations are found on the pages immediately following.

The press set up gage, shown on Dwg #D-115904, was used to align the extrusion dies. The ram of the press was lowered until the punch just entered the die bushing. The gage was then placed on top of the bushing with the two pins in the die cavity. With the pin held firmly against the inside diameter of the die, the gage was rotated around the punch and the deflection of the indicator noted. The die was then shifted until the T.I.R. reading was .002" or less.

The gage shown on Dwg #B-115901 was used to check

## BODY, PROJECTILE, PRACTICE, 30MM

T304 and T241

### INSPECTION GAGING AND PROCEDURES (Cont.)

the concentricity or actual variation in wall thickness. The extruded pieces (both the process pieces and the final "blank") were placed on the rollers and moved against the stop. A long, slender, pointed rod, pivoted at its center point, was placed inside of the shell. The shell was rotated and the variation in wall thickness was measured by a dial indicator which measured the travel of the other end of the pivoted rod.

The gages shown on Dwg #D-115902 and #D-115903 were designed to measure the position of the inside bottom, and the shoulder of the shell with respect to the outside nose diameter.

●  
●  
●  
●  
●  
●  
●  
●  
●  
●  
●

161

[illegible]

100

3.3.3.3

19-00000

2 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100 101 102 103 104 105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200 201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000 1001 1002 1003 1004 1005 1006 1007 1008 1009 1010 1011 1012 1013 1014 1015 1016 1017 1018 1019 1020 1021 1022 1023 1024 1025 1026 1027 1028 1029 1030 1031 1032 1033 1034 1035 1036 1037 1038 1039 1040 1041

3 2 2 4 6 3 2

$\frac{1}{2} \times 6 = 3$  88

100

1. The first group of people who are not allowed to enter the country are those who are not citizens of the United States.

523

[illegible]




9 2 2 2 4

100

5

2000

every one of these : 1. Yes, 2. No, 3. A

[illegible][illegible]

FILE NO.	CHANGE
----------	--------

**Let us be realistic**

14500	14500
-------	-------

50	4300	4
----	------	---

[illegible]

1000

8-15901

1961

2011

1. *Introduction*

**\_\_\_\_\_**



HEWITT MFG. CO. PHILADELPHIA, PA.	CONCENTRICITY .0008 30 W. 130 S. 24 FROSTED SPINDLE, PA. 14
--------------------------------------	---

[illegible]

# BILL OF MATERIALS

NOTE: 1. 2. 3. 4. 5. 6. 7. 8. 9. 10. 11. 12. 13. 14. 15. 16. 17. 18. 19. 20. 21. 22. 23. 24. 25. 26. 27. 28. 29. 30. 31. 32. 33. 34. 35. 36. 37. 38. 39. 40. 41. 42. 43. 44. 45. 46. 47. 48. 49. 50. 51. 52. 53. 54. 55. 56. 57. 58. 59. 60. 61. 62. 63. 64. 65. 66. 67. 68. 69. 70. 71. 72. 73. 74. 75. 76. 77. 78. 79. 80. 81. 82. 83. 84. 85. 86. 87. 88. 89. 90. 91. 92. 93. 94. 95. 96. 97. 98. 99. 100.

QTY	DESCRIPTION	ROUGH SIZE
1	4 1/2 DIA x 3/4 LG	SECRET NO
2	1 2 1/2 DIA x 1 LG	CAP SCREW
3	1 2 1/2 DIA x 3 1/2 LG	ITS
4	1 3/4 DIA x 3 1/2 LG	ITS
5	1 3/4 DIA x 3 1/4 LG	ITS



HARDEN & GRIND

HEINTZ MFG. CO.  
PHILADELPHIA, PA.  
FRANKFORD ARSENAL, PHILA.  
JIG No. J14159

QTY	DESCRIPTION	ROUGH SIZE
1	4 1/2 DIA x 3/4 LG	SECRET NO
2	1 2 1/2 DIA x 1 LG	CAP SCREW
3	1 2 1/2 DIA x 3 1/2 LG	ITS
4	1 3/4 DIA x 3 1/2 LG	ITS
5	1 3/4 DIA x 3 1/4 LG	ITS

## 70

## 71

## BODY, PROJECTILE, PRACTICE, 30MM

T304 and T241

### METALLURGICAL DATA AND DISCUSSION

The stated requirements for these shell included the following mechanical properties:

Yield strength	90,000 psi
Elongation	10%

Previous experience, and the thinking as outlined in the Engineering Considerations section of this report, indicated that a carbon steel of type AISI 1021 was needed to meet these requirements. This steel was purchased from Bethlehem Steel Company and had the following ladle analysis:

Heat No 49N294	
C	- .19
Mn	- .95
P	- .018
S	- .034
Si	- .03

Further examination of this heat of steel established the following facts:

1. Structure: Typical pearlite in a ferrite structure with the ferritic grain size 6-8
2. Hardness: 75-80 R<sub>B</sub>

The shearing operation previously described severely

## BODY, PROJECTILE, PRACTICE, 30MM

T304 and T241

### METALLURGICAL DATA AND DISCUSSION (Cont.)

worked the faces of the slug requiring an anneal to remove this effect so that the pieces might be further cold worked. Several experiments were performed to establish the best annealing cycle. A cycle which consisted of holding the slugs for two (2) hours at 1250° F. was determined to be the most satisfactory in that it softened the surface of the slugs without altering the structure of the steel. Sketches showing the hardness pattern of the billet before and after annealing are found on the pages immediately following the text of this section.

Four factors determine the final mechanical properties of a cold formed shell--(1) the initial mechanical properties of the steel, (2) the type of steel selected, (3) the extent to which the structure of the material is strained, and (4) the choice of the stress relief temperature.

From experience, some theoretical data, and considerable empirical data it is possible to determine, at least approximately, the mechanical properties that will result from various amounts of cold working a given material.

The tensile test curve of a severely cold worked steel specimen which has not been stress relieved shows a very low propor-



# BODY, PROJECTILE, PRACTICE, 30MM

T304 and T241

## METALLURGICAL DATA AND DISCUSSION (Cont.)

tional limit.

The yield strength determined from testing a specimen which has been stress relieved at any temperature other than the optimum will be low, and the full advantage of obtaining this increased strength through strain hardening will not have been realized.

The results of several experiments performed to determine the optimum stress relief temperature are reported below.

<u>Specimen</u>	<u>Stress Relief</u>	<u>Tensile Str.</u>	<u>Yield Str. (.1% Off)</u>	<u>Elong. in 1/2"</u>
<u>T241 SHELL</u>				
1	None	89,750 psi	74,750 psi	12.5%
1A	None	90,000 "	81,000 "	12.5%
2	740° F 30 min.	95,000 "	84,300 "	18.75%
2A	740° F 30 min.	93,500 "	82,500 "	12.5%
3	700° F 45 min.	98,250 "	Bad Test	9.38%
3A	700° F 45 min.	97,000 "	82,700 "	12.5%
<u>T304 SHELL</u>				
4	None	103,000 psi	85,250 psi	12.5%
4A	None	101,500 "	91,000 "	*
5	740° F 30 min.	105,000 "	93,250 "	12.5%
5A	740° F 30 min.	106,100 "	94,500 "	15.63%
6	700° F 45 min.	Not Tested - Mechanical Difficulties		
6A	700° F 45 min.	106,500 "	100,600 "	9.38%

\*Specimen broke through gage mark.

NOTE: Two specimen tested from each shell.

# BODY, PROJECTILE, PRACTICE, 30MM

## T304 and T241

### METALLURGICAL DATA AND DISCUSSION (Cont.)

These results were disappointing and inconsistent with previous experience. The Metallurgical Laboratory of Frankford Arsenal in Philadelphia kindly agreed to further check specimen from these same shell. These results are listed as follows:

<u>Specimen</u>	<u>Stress Relief</u>	<u>Tensile Str.</u>	<u>Yield Str. (.1% Off)</u>	<u>Elong. in 1/2"</u>
<u>T241 SHELL</u>				
1A	None	124,100 psi	110,800 psi	10.0%
1B	None	122,900 "	117,700 "	10.0%
2A	700° F 45 min.	118,300 "	116,500 "	10.4%
2B	700° F 45 min.	119,600 "	114,600 "	9.6%
3A	740° F 30 min.	108,700 "	109,100 "	10.8%
3B	740° F 30 min.	117,000 "	112,400 "	10.0%

#### T304 SHELL

4A	None	101,700 psi	88,300 psi	10.4%
4B	None	103,600 "	99,300 "	10.0%
5A	700° F 45 min.	107,600 "	97,100 "	10.8%
5B	700° F 45 min.	104,200 "	97,200 "	10.4%
6A	740° F 30 min.	107,000 "	99,700 "	11.2%
6B	740° F 30 min.	106,700 "	98,200 "	11.2%

A comparison of these data indicate an extreme variation in results. The data obtained by Heintz indicated that the yield strength was slightly lower than the required 90,000 psi while the Arsenal's results show yield strength considerably in excess of that required. Metallurgists of both parties were unable to explain these

BODY, PROJECTILE, PRACTICE, 30MM

T304 and T241


METALLURGICAL DATA AND DISCUSSION (Cont.)

discrepancies which probably reflect the practical mechanical difficulties attendant upon the testing of such small specimen.


BY THW DATE 5/3/54 SUBJECT 30 MM SHELL  
 CHKD. BY \_\_\_\_\_ DATE \_\_\_\_\_ 241 2304 SHELL

SHEET NO. \_\_\_\_\_ OF \_\_\_\_\_  
 JOB NO. \_\_\_\_\_

# HARDNESS SURVEYS OF SHEARED BILLETS HARDNESS READINGS RB SCALE




# HARDNESS SURVEY OF SHEARED BILLET ANNEALED AT 1450 FOR 2 HOURS HARDNESS READINGS RB SCALE






BY NMM DATE 5/3/54 SUBJECT 30 MM SHELL SHEET NO.        OF         
 CHKD. BY        DATE        T 241 SHELL JOB NO.         
       HARDNESS PATTERNS       


HARDNESS READINGS RM SCALE




SIZED PIECE



1ST BACKWARD EXTRUSION



2ND BACKWARD EXTRUSION





NOSD PIECE

SLUG ANNEALED BEFORE SIZING OPERATION, NO OTHER ANNEALS.

BY 7/11/14 DATE 8/3/57  
CHKD. BY \_\_\_\_\_ DATE \_\_\_\_\_


SUBJECT 30 MM SHELL  
T241 & T304 SHELL  
TENSILE TEST SPECIMENS

SHEET NO. \_\_\_\_\_ OF \_\_\_\_\_  
JOB NO. \_\_\_\_\_



SPECIMEN LOCATION

T 304 SHELL



SPECIMEN LOCATION

T 241 SHELL

BODY, SHELL, HEI, 30MM, T306E10



ENGINEERING CONSIDERATIONS

The shape of this shell with the heavy wall thickness in the open end necessitated using operations such as forward extrusion or draws which would thin the wall in the lower end of the shell leaving the heavy open end undisturbed. Therefore, it was possible to depict the operation designated as first draw on a sequence of operations Dwg #E-120471 which follows immediately after the text on Engineering Considerations.

This piece designated as first draw had to meet the mechanical property requirements of 90,000 psi yield minimum and 10% elongation, since at this stage all of the heavy operations would have been performed.

These mechanical properties were derived from the cold work done following the last process anneal. A process anneal had to follow the backward extrusion operation, since the metal was so severely worked that little ductility remained. Therefore, the shape of the piece which must have the proper yield strength was known, as well as the required reduction in area necessary to produce it. With this knowledge it was then possible to determine the shape of the theoretical backward extruded piece. This theoretical shape was

ENGINEERING CONSIDERATIONS (Cont.)

- . then analyzed to determine what reduction in area was required to produce it and if the reduction was not excessive this theoretical shape became the actual backward extruded shape.

The billet size could then be determined in that the outside diameter of the backward extruded piece required that the outside diameter of the billet be the nearest commercially available bar size. The height of the billet was calculated using this diameter and the knowledge of the required volume of metal in the finished shell.

The operations between backward extrusion and first draw had then to be considered. The shape and the required reduction almost dictated that a forward extrusion, with its great capacity for heavy reductions, be used. The first draw could then be a relatively light operation which could be used advantageously to form the outside and inside diameters to their required sizes.

If the first draw piece were nosed to form the finished shape of the shell, the required force would stress the thin walled section to a value in excess of its yield point and this thin wall would upset. The method used to solve this problem was to employ two operations so designed that in neither was the load required sufficient to yield the thin wall. Such an operation is shown on Dwg #E-120471

BODY, SHELL, HEI, 30MM, T306E10  
ENGINEERING CONSIDERATIONS (Cont.)

and designated as second draw.

Economic considerations demanded that the billet be sheared rather than sawed from the bar stock. Therefore, an anneal was required to remove the effects of the shearing and another press operation had to be employed to shape this distorted sheared slug and form the 1.408" outside diameter.

Before the sheared billet could be sized it was necessary to remove the mill scale from the outside diameter and any burrs caused by the shearing and, of course, to surface treat the piece.

Thus the complete theoretical or basic sequence of cold forming operations was:

1. Shear Billet
2. Tumble
3. Anneal
4. Wheelabrator
5. Surface Treat
6. Size
7. Surface Treat
8. Backward Extrude
9. Anneal
10. Surface Treat
11. Forward Extrude
12. First Draw
13. Second Draw
14. Nose
15. Stress Relieve

BODY, SHELL, HEI, 30MM, T306E10

ENGINEERING CONSIDERATIONS (Cont.)

With this information the tools necessary to form the required shape could be designed and built, and all gages, jigs, and auxiliary equipment for surface treating could be made.

These operations will now be discussed in detail with regard for the practical tooling, metallurgical, chemical and manufacturing problems.



BODY, SHELL, HEI, 30MM, T306E10

COLD FORMING OPERATIONS

1. SHEAR BILLET

The tools necessary to shear the 1-1/4" bar stock are shown on Dwg #B-114782 (p. 20).

The bar stock was manually fed into the die during the up stroke of the press, and the billets fell out below the die.

This operation was identical in detail to that described for the T241 and T304 bodies with the exception of adjusting the stop to make the billet of the required weight of 2,800 grains for this particular shell.

The die was run on a 100 ton Verson mechanical press. The actual tonnage required was 43 tons.

BODY, SHELL, HEI, 30MM, T306E10

COLD FORMING OPERATIONS (Cont.)

2. TUMBLE BILLETS

The purpose of this procedure was to remove any sharp edges and burrs from the faces of the sheared billet. A distorted slug, as produced by shearing, did not lend itself to automatic chamfering of the billet edges, and a manual grinding operation to remove burrs was economically prohibitive.

Tumbling was an economical operation in that only a part-time operator was required to load and unload the tumbler, of one thousand (1,000) pieces in a cycle time of forty-five (45) minutes.

BODY, SHELL, HEI, 30MM, T306E10

COLD FORMING OPERATIONS (Cont.)

3. ANNEAL BILLETS

If the billet were to be further cold worked it was imperative that the original ductility be restored to the severely worked sheared surface. An anneal was therefore required. This thermal treatment also minimized the piece-to-piece and bar-to-bar differences in hardness, and thereby enhanced the repetitive accuracy of the cold forming operations.

The billets were heated to a temperature of 1275° F. in a Lindberg Electric Furnace, soaked at this temperature for one and one-half (1-1/2) hours and air cooled.

Reference should be made to the section on Metallurgical Data which shows the effect of this anneal on the hardness of the sheared billet.



BODY, SHELL, HEI, 30MM, T306E10

COLD FORMING OPERATIONS (Cont.)

4. SHOTBLAST

It was virtually impossible to have an automatic surface treating cycle that was compatible with the tenacious scale found on the surface of hot rolled bars, and the smooth, clean surface of pieces that had been previously extruded. The most economical method of removing this scaled surface was mechanical blasting.

These pieces were "wheelabrated" on a tumble blast machine manufactured by American Wheelabrator Corporation, using soft "nail whiskers" as shot. It was very important that soft shot of some kind be used as hard shot tended to imbed itself in the relatively soft billet and would score the die used to form it.

BODY, SHELL, HEI, 30MM, T306E10

COLD FORMING OPERATIONS (Cont.)

5. SURFACE TREAT BILLETS

This surface treatment, or "Foscoating", operation was done on the Heintz experimental, manual Foscoating line. The pieces were placed in stainless steel trays by an operator and then were carried in baskets through the chemical cycle which follows:

1. Alkaline clean
2. Cold water rinse
3. Sulphuric acid pickle
4. Cold, overflowing water rinse
5. Hot, overflowing water rinse
6. Foscoat
7. Cold, overflowing water rinse
8. Hot, overflowing water rinse
9. Lubrication

Chemicals were supplied by Pennsylvania Salt Manufacturing Company of Philadelphia.

A complete description of the chemical constituents and process controls is contained in the appendix section entitled "Chemical Data".

BODY, SHELL, HEI, 30MM, T306E10

COLD FORMING OPERATIONS (Cont.)

6. SIZE BILLET

The tools necessary to perform this operation are shown on Dwg #D-119843-1 which immediately follows the text describing this operation.

Since all billets were sheared from 1-1/4" bar stock, this sizing operation, in addition to its usual function of shaping the distorted slug, also expanded its diameter to the required 1-1/2".

As previously described, the punch (Item #7), the bushing (Item #8), and the knockout pin (Item #18) were the actual forming elements of this die. These parts were so designed as to be interchangeable with the remainder of the assembly. This assembly was then suitable not only for this operation but for all subsequent extrusions.


The only difficulty experienced with the die other than the usual alignment problems was the exceedingly critical nature of the press shut height adjustment. This was nearly a confined die and too low a setting of the shut height would have resulted in complete confinement and excessive tool stresses.

BODY, SHELL, HEI, 30MM, T306E10

COLD FORMING OPERATIONS (Cont.)

SIZE BILLET (Cont.)

The operation was performed on a Verson press rated at 100 tons 6" up from bottom dead center. The actual tonnage required for this operation was 233 tons.



ROUND

POLISH BEFORE HANDLING & AFTER  
MUST BE FREE OF NICKS, SCRATCHES & TOOL MARKS

PUNCH

MATERIAL - STAINLESS STEEL  
HARDEN - Rc 59-60

NOTE:-  
USE WITH DIE # 24934  
CHANGE PUNCH ONLY

FILE NO.	CHANGE
DATE	10/10/2
SO. E	4.07-5
NO. 46651	
D-119843-1	
DIE NO.	D-24953

HEINTZ MFG. CO. MELROSE, MA.										DIE PART DETAILS (SIZE) 30 MM. T306E10 - FD-18083 PUNCH/POD ANNUAL									
A																			
B																			
C																			
D																			
E																			
F																			
G																			
H																			
I																			
J																			
K																			
L																			
M																			
N																			
O																			
P																			
Q																			
R																			
S																			
T																			
U																			
V																			
W																			
X																			
Y																			
Z																			

BODY, SHELL, HEI, 30MM, T306E10

COLD FORMING OPERATIONS (Cont.)

7. SURFACE TREAT SIZED PIECE

This operation was identical with Operation #5.

It was always necessary to coat prior to a backward extrusion operation. Backward extrusion caused the coating to stretch, at least locally, as much as 800%, and anything less than a proper coating would not withstand such severe treatment.

BODY, SHELL, HEI, 30MM, T306E10

COLD FORMING OPERATIONS (Cont.)

8. BACKWARD EXTRUDE

The tools required to backward extrude this shell are shown on Dwg #D-119844 which immediately follows the text of this section.

As with the previously described dies, the punch, bushing and knockout pin were the actual forming elements which were designed as replaceable parts of the complete die assembly.

This die, like all extrusion dies, had to be very carefully aligned because this operation, in addition to drastically forming the metal, also determined the concentricity of the piece which had to be held within .008" T.I.R.

The billet was placed in the die and the punch forced it down to the knockout pin and then stressed the metal to the point where it flowed upward through the annular orifice between punch and bushing. The press shut height was set to give the required bottom thickness of .180 to .185". This dimension, as well as eccentricity, was carefully checked when setting this die and at frequent intervals when the die was running.

BODY, SHELL, HEI, 30MM, T306E10

COLD FORMING OPERATIONS (Cont.)

BACKWARD EXTRUDE (Cont.)

This operation was performed on a 100 ton Verson single point suspension press. The required force to form this piece was 125 tons.







9. ANNEAL

The very severely cold worked backward extruded piece was annealed to restore sufficient ductility to allow further cold forming.

A sub-critical anneal which restored the original softness and ductility without changing the structure of the metal was used.

The pieces were heated to a temperature of 1150° F. in a Lindberg Electric Furnace, soaked at this temperature for one and one-half (1-1/2) hours, and air cooled.

The results of this anneal may best be understood by referring to the sketches showing the hardness of the material before and after this thermal treatment. These sketches are found in the section on Metallurgical Data.

BODY, SHELL, HEI, 30MM, T306E10

COLD FORMING OPERATIONS (Cont.)

10. SURFACE TREAT

This operation was identical to the surface treating previously described with the exception that some provision had to be made to oscillate the pieces to expel the air from the cavity. This was accomplished by placing pieces in a basket that was rotated about  $30^{\circ}$  on either side of the horizontal position.

BODY, SHELL, HEI, 30MM, T306E10

COLD FORMING OPERATIONS (Cont.)


11. FORWARD EXTRUDE

Basically, forward extrusion was accomplished by placing a backward extruded "cup" into a die and using a punch which pressed on the top of the piece.

This operation was performed in the above described manner and the depth to which the punch entered the die determined the length of the thick walled section at the open end of the shell. This distance from the bottom of the shell to the extrusion shoulder had to be 1-1/2" plus 1/16 minus 0. The pieces were checked to assure the concentricity of .008 maximum was not increased by this operation.

The tooling required to make this piece is shown on Dwg #B-119845.

This die was run on a 100 ton mechanical Verson press although the required force was only 60 tons.



HERTZ MFG. CO.  
P.O. BOX 1000  
MILWAUKEE, WIS. 53201

FORWARD TO: HERTZ MFG. CO.  
P.O. BOX 1000  
MILWAUKEE, WIS. 53201

DATE: 11/11/84  
BY: [Signature]

FILE NO: 119845  
DATE: 11/11/84









BODY, SHELL, HEI, 30MM, T306E10

COLD FORMING OPERATIONS (Cont.)

12. FIRST DRAW AND COIN

This press operation formed the cavity shape and reduced the outside diameter by drawing the metal in against the punch in the lower section and ironing the upper wall.

Drawing, of course, introduced tensile stress in the piece and tended to make the bottom of the piece slightly curved. A coining operation, which consisted simply of compressing the metal between the punch and knockout pin, at the end of the draw stroke, removed this curvature and produced a flat bottom of .165" plus or minus .003" as required. The press shut height was adjusted so that the distance from the draw angle to the bottom of the piece was 1-7/8".

The tooling used to form the metal as described is shown on Dwg #B-119846 which immediately follows this text. The operation was done on a 100 ton mechanical Verson press. The force actually necessary was 105 tons for coining. The draw load itself was only 11 tons.

Part No.	Qty	Unit Price	Total Price
1	1	1.00	1.00
2	1	1.00	1.00
3	1	1.00	1.00
4	1	1.00	1.00
5	1	1.00	1.00
6	1	1.00	1.00
7	1	1.00	1.00
8	1	1.00	1.00
9	1	1.00	1.00
10	1	1.00	1.00
11	1	1.00	1.00
12	1	1.00	1.00
13	1	1.00	1.00
14	1	1.00	1.00
15	1	1.00	1.00
16	1	1.00	1.00
17	1	1.00	1.00
18	1	1.00	1.00
19	1	1.00	1.00
20	1	1.00	1.00
21	1	1.00	1.00
22	1	1.00	1.00
23	1	1.00	1.00

Part No.	Qty	Unit Price	Total Price
1	1	1.00	1.00
2	1	1.00	1.00
3	1	1.00	1.00
4	1	1.00	1.00
5	1	1.00	1.00
6	1	1.00	1.00
7	1	1.00	1.00
8	1	1.00	1.00
9	1	1.00	1.00
10	1	1.00	1.00
11	1	1.00	1.00
12	1	1.00	1.00
13	1	1.00	1.00
14	1	1.00	1.00
15	1	1.00	1.00
16	1	1.00	1.00
17	1	1.00	1.00
18	1	1.00	1.00
19	1	1.00	1.00
20	1	1.00	1.00
21	1	1.00	1.00
22	1	1.00	1.00
23	1	1.00	1.00



Part No.	Qty	Unit Price	Total Price
1	1	1.00	1.00
2	1	1.00	1.00
3	1	1.00	1.00
4	1	1.00	1.00
5	1	1.00	1.00
6	1	1.00	1.00
7	1	1.00	1.00
8	1	1.00	1.00
9	1	1.00	1.00
10	1	1.00	1.00
11	1	1.00	1.00
12	1	1.00	1.00
13	1	1.00	1.00
14	1	1.00	1.00
15	1	1.00	1.00
16	1	1.00	1.00
17	1	1.00	1.00
18	1	1.00	1.00
19	1	1.00	1.00
20	1	1.00	1.00
21	1	1.00	1.00
22	1	1.00	1.00
23	1	1.00	1.00

NOTE:-

- 1- PARTS ITEM NOS 1, 2, 3, 4, 5, 6, 9, 10, 11, 12, 13, 14, 16, 17, 18, 19, 20, 21, 22, & 23 ARE **NOT** TO BE MADE FOR THIS DIE.
- 2- Use Surplus Parts From Die No D 24294, Due No B 119824 & Details

Part No.	Qty	Unit Price	Total Price
1	1	1.00	1.00
2	1	1.00	1.00
3	1	1.00	1.00
4	1	1.00	1.00
5	1	1.00	1.00
6	1	1.00	1.00
7	1	1.00	1.00
8	1	1.00	1.00
9	1	1.00	1.00
10	1	1.00	1.00
11	1	1.00	1.00
12	1	1.00	1.00
13	1	1.00	1.00
14	1	1.00	1.00
15	1	1.00	1.00
16	1	1.00	1.00
17	1	1.00	1.00
18	1	1.00	1.00
19	1	1.00	1.00
20	1	1.00	1.00
21	1	1.00	1.00
22	1	1.00	1.00
23	1	1.00	1.00


Page 1 of 1



Q

215


MATERIAL: 3-20-54 QHTS  
E-54-56



HIGHLY POLISH BEFORE HARDENING & AFTER.  
'JUST BE FREE OF NICKS, SCRATCHES, TOOL MARKS,  
& UNDERCUTS

2

MATERIAL - STAINLESS STEEL  
HARDEN - Rc 59-60



KNOCK - OUT

MATERIAL - STAMINAL CHTS

HOW - R<sub>c</sub> 57-59

15

[illegible]

BODY, SHELL, HEI, 30MM, T306E10

COLD FORMING OPERATIONS (Cont.)

13. SECOND DRAW


This "draw" operation actually folded the metal in the large walled section at the open end into the inside of the piece, producing a uniform outside diameter.

Considerable difficulty was experienced with this operation. Any punch used to draw the piece through the die had to be small enough to be removed through the reduced inside nose diameter created by this operation. A punch of this diameter created a pressure on the inside bottom of the piece sufficient to malform it.

This problem was solved by making a very unique punch as shown on Dwg #119848. This punch pressed on the top of the piece and as it pushed through the die it collapsed to conform to the decreasing die diameter.

The necessary tools are shown on Dwg #119848. Only 44 tons were required to do this operation.

SEE NOTE NO.		BILL OF MATERIALS	
		DETAIL DWG NO	ROUGH SIZE
		D-11984-2	1
		D-11984-4	2
		D-11984-7	3
		D-11984-4	4
		D-11984-2	5
		D-11984-1	6
		D-11984-1	7
		D-11984-1	8
		D-11984-3	9
		OMIT	10
		D-11984-1	11
		D-11984-1	12
		D-11984-1	13
		D-11984-1	14
		D-11984-1	15
		D-11984-1	16
		D-11984-1	17
		D-11984-1	18
		D-11984-1	19
		D-11984-1	20
		D-11984-1	21
		D-11984-1	22
		D-11984-1	23



NOTE:-



1 PARTS ITEMS NO 1, 2, 3, 4, 5, 6, 8, 9, 10, 11 ARE NOT TO BE MADE FOR THIS DIE

2 - USE WRENCH ASSEMB FROM DIE NO 24224


PRESS DIE

HENTZ MFG. CO. Pittsburgh, Pa.		NOTE DIE NO. 24224 80 H.P. T-318 PITTSBURGH, PA.		B-119845		D-24958	
DATE: 1-25-54		BY: J. H. H.		FILE NO. 41481		CHECKED: 41481	
1-25-54		1-25-54		1-25-54		1-25-54	






81

[illegible]

22

33

7-560



23;

9. 3. 5.

[illegible]





BODY, SHELL, HEI, 30MM, T306E10

COLD FORMING OPERATIONS (Cont.)

14. NOSE

The tools required to nose this shell are shown on Dwg #B-119847 which immediately follows.


The cylindrical piece previously formed was placed mouth down in the die and forced to conform to the curved shape of the die as it was pushed down by the punch. The distance to which the piece was pushed into the die was determined by the overall length requirement of 2.750" to 2.770". The outside diameter was to be held between 1.170" and 1.176".

This operation was performed using a 100 ton mechanical Verson press. Only twenty tons were actually necessary to nose this piece.

ITEM NO	DESCRIPTION	QTY	UNIT	REMARKS
1	29471	1	PC	29471
2	30471	1	PC	30471
3	31471	1	PC	31471
4	32471	1	PC	32471
5	33471	1	PC	33471
6	34471	1	PC	34471
7	35471	1	PC	35471
8	36471	1	PC	36471
9	37471	1	PC	37471
10	38471	1	PC	38471
11	39471	1	PC	39471
12	40471	1	PC	40471
13	41471	1	PC	41471
14	42471	1	PC	42471
15	43471	1	PC	43471
16	44471	1	PC	44471
17	45471	1	PC	45471
18	46471	1	PC	46471
19	47471	1	PC	47471
20	48471	1	PC	48471
21	49471	1	PC	49471
22	50471	1	PC	50471
23	51471	1	PC	51471
24	52471	1	PC	52471
25	53471	1	PC	53471
26	54471	1	PC	54471
27	55471	1	PC	55471
28	56471	1	PC	56471
29	57471	1	PC	57471
30	58471	1	PC	58471
31	59471	1	PC	59471
32	60471	1	PC	60471
33	61471	1	PC	61471
34	62471	1	PC	62471
35	63471	1	PC	63471
36	64471	1	PC	64471
37	65471	1	PC	65471
38	66471	1	PC	66471
39	67471	1	PC	67471
40	68471	1	PC	68471
41	69471	1	PC	69471
42	70471	1	PC	70471
43	71471	1	PC	71471
44	72471	1	PC	72471
45	73471	1	PC	73471
46	74471	1	PC	74471
47	75471	1	PC	75471
48	76471	1	PC	76471
49	77471	1	PC	77471
50	78471	1	PC	78471
51	79471	1	PC	79471
52	80471	1	PC	80471
53	81471	1	PC	81471
54	82471	1	PC	82471
55	83471	1	PC	83471
56	84471	1	PC	84471
57	85471	1	PC	85471
58	86471	1	PC	86471
59	87471	1	PC	87471
60	88471	1	PC	88471
61	89471	1	PC	89471
62	90471	1	PC	90471
63	91471	1	PC	91471
64	92471	1	PC	92471
65	93471	1	PC	93471
66	94471	1	PC	94471
67	95471	1	PC	95471
68	96471	1	PC	96471
69	97471	1	PC	97471
70	98471	1	PC	98471
71	99471	1	PC	99471
72	100471	1	PC	100471

NOTE:-

1. PARTS ITEM NO 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100
2. ALTER ITEM NO 15 OF DIE NO 23104 TO READ AS ITEM NO 5 OF THIS DIE
3. SEE WRENCH ASSEM FROM DIE NO 24294
4. SEE DIE NO 24294 PART NOT SHOWN IN ASSEMBLY




ITEM NO	DESCRIPTION	QTY	UNIT	REMARKS
1	29471	1	PC	29471
2	30471	1	PC	30471
3	31471	1	PC	31471
4	32471	1	PC	32471
5	33471	1	PC	33471
6	34471	1	PC	34471
7	35471	1	PC	35471
8	36471	1	PC	36471
9	37471	1	PC	37471
10	38471	1	PC	38471
11	39471	1	PC	39471
12	40471	1	PC	40471
13	41471	1	PC	41471
14	42471	1	PC	42471
15	43471	1	PC	43471
16	44471	1	PC	44471
17	45471	1	PC	45471
18	46471	1	PC	46471
19	47471	1	PC	47471
20	48471	1	PC	48471
21	49471	1	PC	49471
22	50471	1	PC	50471
23	51471	1	PC	51471
24	52471	1	PC	52471
25	53471	1	PC	53471
26	54471	1	PC	54471
27	55471	1	PC	55471
28	56471	1	PC	56471
29	57471	1	PC	57471
30	58471	1	PC	58471
31	59471	1	PC	59471
32	60471	1	PC	60471
33	61471	1	PC	61471
34	62471	1	PC	62471
35	63471	1	PC	63471
36	64471	1	PC	64471
37	65471	1	PC	65471
38	66471	1	PC	66471
39	67471	1	PC	67471
40	68471	1	PC	68471
41	69471	1	PC	69471
42	70471	1	PC	70471
43	71471	1	PC	71471
44	72471	1	PC	72471
45	73471	1	PC	73471
46	74471	1	PC	74471
47	75471	1	PC	75471
48	76471	1	PC	76471
49	77471	1	PC	77471
50	78471	1	PC	78471
51	79471	1	PC	79471
52	80471	1	PC	80471
53	81471	1	PC	81471
54	82471	1	PC	82471
55	83471	1	PC	83471
56	84471	1	PC	84471
57	85471	1	PC	85471
58	86471	1	PC	86471
59	87471	1	PC	87471
60	88471	1	PC	88471
61	89471	1	PC	89471
62	90471	1	PC	90471
63	91471	1	PC	91471
64	92471	1	PC	92471
65	93471	1	PC	93471
66	94471	1	PC	94471
67	95471	1	PC	95471
68	96471	1	PC	96471
69	97471	1	PC	97471
70	98471	1	PC	98471
71	99471	1	PC	99471
72	100471	1	PC	100471





THE DUSHINS  
STANDARD OIL CO.  
GRAND OIL  
AND POLISH




N<sup>o</sup> E-2


S. J. - 5960

M. J. - 748


N. J. - 7




③



1900




THE M. J. J. J. J.



8



4



FILE NO.	CHARGE
----------	--------

**ADDRESS ONLY ONE SIDE**

CUST NO

**INSTAL**

100

**D-119847-2**

DIE NO. 24057

DIE FART, DETAILS / NOSE /  
30MM, T30610 - FD - 18083  
FRANKFURT - WISSEN

**HEINTZ MFG. CO.**  
PHILADELPHIA, PA.


[illegible]

1


2	3

--	--	--

11

11

7	3

1	2
3	4

11

11


১৫	১৬

1378

Year	Days
1990	1
1991	1
1992	1
1993	1
1994	1
1995	1
1996	1
1997	1
1998	1
1999	1
2000	1
2001	1
2002	1
2003	1
2004	1
2005	1
2006	1
2007	1
2008	1
2009	1
2010	1
2011	1
2012	1
2013	1
2014	1
2015	1
2016	1
2017	1
2018	1
2019	1
2020	1
2021	1
2022	1
2023	1
2024	1
2025	1
2026	1
2027	1
2028	1
2029	1
2030	1
2031	1
2032	1
2033	1
2034	1
2035	1
2036	1
2037	1
2038	1
2039	1
2040	1
2041	1
2042	1
2043	1
2044	1
2045	1
2046	1
2047	1
2048	1
2049	1
2050	1
2051	1
2052	1
2053	1
2054	1
2055	1
2056	1
2057	1
2058	1
2059	1
2060	1
2061	1
2062	1
2063	1
2064	1
2065	1
2066	1
2067	1
2068	1
2069	1
2070	1
2071	1
2072	1
2073	1
2074	1
2075	1
2076	1
2077	1
2078	1
2079	1
2080	1
2081	1
2082	1
2083	1
2084	1
2085	1
2086	1
2087	1
2088	1
2089	1
2090	1
2091	1
2092	1
2093	1
2094	1
2095	1
2096	1
2097	1
2098	1
2099	1
2100	1
2101	1
2102	1
2103	1
2104	1
2105	1
2106	1
2107	1
2108	1
2109	1
2110	1
2111	1
2112	1
2113	1
2114	1
2115	1
2116	1
2117	1
2118	1
2119	1
2120	1
2121	1
2122	1
2123	1
2124	1
2125	1
2126	1
2127	1
2128	1
2129	1
2130	1
2131	1
2132	1
2133	1
2134	1
2135	1
2136	1
2137	1
2138	1
2139	1
2140	1
2141	1
2142	1
2143	1
2144	1
2145	1
2146	1
2147	1
2148	1
2149	1
2150	1
2151	1
2152	1
2153	1
2154	1
2155	1
2156	1
2157	1
2158	1

176

新



BODY, SHELL, HEI, 30MM, T306E10

COLD FORMING OPERATIONS (Cont.)

15. STRESS RELIEVE

After considerable experimental work a temperature of 700° F. was found to be the desired stress relief temperature. The pieces were heated in a Lindberg Electric Furnace and held for one and one-half (1-1/2) hours at this temperature and then air cooled.

BODY, SHELL, HEI, 30MM, T306E10

MACHINING AND FINISHING OPERATIONS

Operations necessary to finish the cold extruded shell, although conventional in nature, are recorded in detail hereafter.

All of these operations were done at Pantex Manufacturing Corporation, Pawtucket, Rhode Island, on automatic equipment now in use to produce 30mm shell bodies from bar stock.

The operations were as follows:

1. Rough Face and Drill
2. Face, Drill and Recess Nose End of Shell
3. Machine 1/8" Radius at Junction of Outside Diameter and Base
4. Wash
5. Tap 3/4"-20 thread
6. Wash
7. Spot Weld Base Plate
8. Inspect
9. Pack

A sketch showing the cold extruded blank prior to machining and indicating the metal to be removed is shown on the following page.



<div style="display: flex; justify-content: space-between;"> <div> <p>020 APPROX.</p> <p>1/8 APPROX.</p> </div> <div> </div> <div> <p>19/32 DIA. APPROX.</p> </div> </div>																																																														
<p style="text-align: center;">SHADED AREA TO BE MACHINED AWAY OTHER SURFACES ARE FINISHED.</p>																																																														
<table border="1" style="width: 100%;"> <tr> <td colspan="4">HEINTZ MFG. CO. PHILADELPHIA, PA.</td> <td colspan="4">APPROXIMATE EXCESS METAL ON SHELL BODY FD 18083A 30MM, T306E10 - FRANKFORD ARSENAL</td> <td colspan="5" rowspan="2">E-119836</td> </tr> <tr> <td colspan="2">DRAWN JER 9-15-54</td> <td colspan="2">TRACED</td> <td colspan="2">CHECKED A. J. E. 9-16-54</td> <td colspan="2">APPROVED</td> </tr> </table>													HEINTZ MFG. CO. PHILADELPHIA, PA.				APPROXIMATE EXCESS METAL ON SHELL BODY FD 18083A 30MM, T306E10 - FRANKFORD ARSENAL				E-119836					DRAWN JER 9-15-54		TRACED		CHECKED A. J. E. 9-16-54		APPROVED																														
HEINTZ MFG. CO. PHILADELPHIA, PA.				APPROXIMATE EXCESS METAL ON SHELL BODY FD 18083A 30MM, T306E10 - FRANKFORD ARSENAL				E-119836																																																						
DRAWN JER 9-15-54		TRACED		CHECKED A. J. E. 9-16-54		APPROVED																																																								
<table border="1" style="width: 100%;"> <tr> <td colspan="12">ASSEMBLIES ON UNIT</td> <td rowspan="4">FILE NO.</td> <td rowspan="4">CHANGE</td> </tr> <tr> <td colspan="12">CUST. NO.</td> </tr> <tr> <td colspan="12">METAL</td> </tr> <tr> <td colspan="12">NO. REQ.</td> </tr> </table>													ASSEMBLIES ON UNIT												FILE NO.	CHANGE	CUST. NO.												METAL												NO. REQ.											
ASSEMBLIES ON UNIT												FILE NO.	CHANGE																																																	
CUST. NO.																																																														
METAL																																																														
NO. REQ.																																																														

## MACHINING AND FINISHING OPERATIONS (Cont.)

1. ROUGH FACE AND DRILL


This operation was performed in a 1-1/2 x 8 Conematic Chucker Serial No 3319WW. The details pertinent to this operation are shown below in tabular form. Tool drawings are found on the pages immediately following this text.

Steel Spec.	SAE 1021	Spindle Gears	33/39
Collet Size	1-3/16	Feed Gears	24/54
SSFPM	100	Tool Slide Cam Rise	5/8
Spindle RPM	361	Front Cross Slide Cam Rise	1/4
Cycle	16	Rear Cross Slide Cam Rise	0
Hourly Production	126		

POS	TOOL SLIDE OPERATIONS	POS	CROSS SLIDE OPERATIONS
1		1	
2		2	
3		3	Face with T312E1-T-25 tool in T-158-T-9 holder
4		4	
5		5	
6		6	
7	Insert shell with auxiliary arm (standard)	7	Mount gravity feed magazine (standard)
8	Drill cavity to 5/8 dia. with standard 5/8 three lip stub drill	8	

As a coolant a 20:1 mixture of Houghton Antisep All Purpose Base and water was used.





# BODY, SHELL, HEI, 30MM, T306E10

## MACHINING AND FINISHING OPERATIONS (Cont.)

### 2. FACE, DRILL AND RECESS NOSE END OF SHELL

This machining was done on a 1-1/2" Conematic Chucker, Serial No 3319WW. The pertinent details such as speed, feeds, tools, etc., are shown in tabular form below:

Steel Spec.	1021	Spindle Gears	33/39
Collet Size	1-3/16	Feed Gears	38/40
SSFPM	100	Tool Slide Cam Rise	5/8
Spindle RPM	361	Front Cross Slide Cam Rise	1/4
Cycle	35	Rear Cross Slide Cam Rise	0
Hourly Production	60		

POS	TOOL SLIDE OPERATIONS	POS	CROSS SLIDE OPERATIONS
1	Drill .770 c/b dia. (rough) with st'd 3/4 three lip stub drill	1	
2	Drill (rough) minor pitch dia. with st'd 11/16 three lip stub drill	2	Rough face 15° angle with T312E1-T-25 breakdown tool in T158-T-9 holder
3	Ream .770 c/b dia. finish with st'd 25/32 dia. six flute stub reamer (ground to .774 dia.)	3	Finish face 15° angle with T-158-T-5 blade in T-158-T- 11 tool holder
4	Recess with internal recessing attachment. Recessing tool T306E10-T-10	4	
5	Ream minor pitch dia. finish with st'd 23/32 dia. six flute reamer ground to .6995 dia.	5	
6		6	
7	Insert shell with st'd auxiliary arm	7	Mount standard gravity feed magazine
8		8	

BODY, SHELL, HE1, 30MM, T306E10

MACHINING AND FINISHING OPERATIONS (Cont.)

2. FACE, DRILL AND RECESS NOSE END OF SHELL (Cont.)

The coolant was the E. F. Houghton Company's Antisept  
All Purpose Base mixed with water in the ratio of 20:1.

This machine was powered by a 25 HP, 220 volt, 60  
cycle, 3 phase, 1750 RPM motor.

The tools are shown on the pages immediately following  
this text.











BODY, SHELL, HEI, 30MM, T306E10

MACHINING AND FINISHING OPERATIONS (Cont.)

3. MACHINE 1/8" RADIUS AT JUNCTION OF OUTSIDE DIAMETER  
AND BASE

A Rapiduction Hand Screw Machine built by the Oster Manufacturing Company of Cleveland, Ohio, was used to form the radius.

The details of this machining setup are listed below in tabular form.

1. Collet Size	1-3/16
2. Spindle Speed	286 RPM
3. Manual Cycle	
4. Production Rate	150 pcs/hr

The machine was powered by a 4 HP, 220 volt, 60 cycle, 3 phase, 1700 RPM electric motor. A high speed tool bit 1/2" square by 4" long was used, ground according to Heintz SK #10955 which is shown on the page immediately following this text.

The operation was manual. The operator placed the piece in the collet, brought the tool against the shell until the radius was formed, then removed the tool, stopped the machine and removed the piece from the collet.



MACHINING AND FINISHING OPERATIONS (Cont.)

4. WASH

The machine used was a Blakeslee Metal Parts Washer of a single stage conveyor type, serial No 1138, manufactured by G. S. Blakeslee & Company of Chicago, Illinois.

The pieces were placed open end down in welded wire baskets which held fifty (50) pieces each. As the pieces were carried through the machine by the conveyor they were sprayed with an emulsion cleaner and a rust inhibitor.

The chemicals used were NAMUL (emulsion cleaner) and SR-12 (rust inhibitor) which were manufactured by the Angler Chemical Company of Norton, Massachusetts.

The NAMUL was mixed in the ratio of one (1) gallon to one hundred seventy-five (175) gallons of water and the SR-12 was used at the ratio of four (4) ounces to one hundred seventy-five (175) gallons of water. The temperature of the spray was maintained at 175° F.

BODY, SHELL, HEI, 30MM, T306E10  
MACHINING AND FINISHING OPERATIONS (Cont.)

5. TAP 3/4"-20 THREAD

A Kaufman tapping machine, Serial #10-188, with a capacity of 5/8" to 1-1/8" manufactured by the L. J. Kaufman Manufacturing Company of Manitowok, Wisconsin, was used. The machine setup is listed below:

1. Motor	3 HP, 220 volt, 3 phase, 60 cycle, 1725 RPM
2. Coolant	Trifalex (undiluted)
3. Production Rate	200 pcs/hr
4. Spindle Speed	400 RPM
5. Lead Screw	20 pitch, left hand

The operator placed two shell in the loading position of an eight station rotary table. The table then indexed and tapped two bodies simultaneously. While the machine operated, the operator removed two finished shell and replaced them with two new ones. The cycle was then repeated. An undiluted cutting oil manufactured by Trifalex Corporation of New York City was applied by brush to the area to be tapped.

BODY, SHELL, HEI, 30MM, T306E10

MACHINING AND FINISHING OPERATIONS (Cont.)

6. WASH

This operation was identical to operation #4.

BODY, SHELL, HEI, 30MM, T306E10

MACHINING AND FINISHING OPERATIONS (Cont.)

7. SPOT WELD BASE PLATE

A production welder manufactured by the Thomson-Gibb Electric Welding Company of Lynn, Massachusetts, welded the base plate to the bottom of the shell.

The machine specifications are listed below:

1. Thomson Production Welder, Type 19Z, Serial #15055
2. Electrical rating: 75 KVA, 60 cycle, primary voltage 220, primary current 341 amps, secondary current 42, 500 amps
3. Ignition timer: Westinghouse Electric Company's type SP 11B, 220 volt and 440 volt, 60 cycle, style 1106263.

The operator placed the shell open end down in a vise-like opening. A rubber centering device was placed on the piece and then the base plate was put into the cavity in the centering device. A switch was activated and the plate was welded in. The shell body was then removed and the cycle repeated.



BODY, SHELL, HEI, 30MM, T306E10

MACHINING AND FINISHING OPERATIONS (Cont.)

8. INSPECT


The following gages were used to check this shell body.

1. Length gage (press)	J-15147
2. Thread gages	J-15734
3. 1.176 dia. snap gage	J-15712
4. 2.77 overall length snap gage	J-15714
5. .965 nose diameter	J-15716
6. .920-.930 plug gage	J-15717
7. .990-1.000 plug gage	J-15718
8. .500 thread length gage	J-15721
9. .6959/.7037 plug gage	J-15735

All of these gages are standard with the exception of  
Item #5 and 8, which are shown on the following pages.

# BILL OF MATERIALS

NOTE	QTY	UNIT	ROUGH SIZE
1	3	3	1/4 DIA x 3/4 LG
2	1	1	2 1/2 DIA x 1 LG
3	1	1	2 1/2 DIA x 3 1/4 LG



1 1/4 - 120

2 1/2 - 120

HARDEN & GRIND ALL PARTS

A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V

HEINTZ MFG. CO.  
PHILADELPHIA, PA.

LENGTH GAGE  
30MM T306E10  
FRANKFORD ARSENAL

DATE 11-1-54  
BY J.E. S.A.

FILE NO. CHANGE

108102  
4017-11  
46714

D-12117  
J-15147

[illegible]

[illegible]

BODY, SHELL, HEI, 30MM, T306E10

MACHINING AND FINISHING OPERATIONS (Cont.)

9. PACK

The pieces were packed according to specification MIL-P-10025A.

The box was made from 1/8" double faced corrugated cardboard and was 12-3/4" long by 6-3/8" wide by 9-1/4" deep and held one hundred (100) shell bodies in two layers of fifty each. The individual bodies were placed inside the spaces created by a 1/32" thick smooth cardboard separator. This separator was of the egg crate variety and formed pockets to hold five (5) shell along the width and ten (10) shell along the length of the box. A flat piece of 1/8" double face corrugated cardboard was used to separate the layers.

NOTE: In accordance with the instructions of the contract, these pieces were neither banded nor painted.

BODY, SHELL, HEI, 30MM, T306E10  
METALLURGICAL DATA AND DISCUSSION

The mechanical properties required in this shell were a minimum yield strength of 90,000 psi and an elongation of 10%.

This shell was made from the same 1-1/4" diameter AISI 1021 hot rolled bars as was used to make shell T241 and T304. The properties were identical and are repeated here for convenience only.

Chemical Analysis:

C	-	.19
Mn	-	.95
P	-	.018
S	-	.034
Su	-	.03

Structure: typical pearlite in a ferritic structure.  
Grain size 6-8.

Hardness: 70-80 R<sub>B</sub>

After considerable experimental work had been performed it was agreed that a temperature of 700° F. produced the optimum results. The thinking and experimental work done was identical to that explained in detail on page 72.

The results of the tensile test obtained by pulling a flat specimen (see page 145) are listed below.

BODY, SHELL, HEI, 30MM, T306E10

METALLURGICAL DATA AND DISCUSSION (Cont.)

<u>Specimen</u>	<u>Tensile Strength</u>	<u>Yld. Str. (.1% Off)</u>	<u>Elong. in 1/2"</u>	<u>Hardness Range</u>
3-2	98,500	94,100	12.5%	99-101
4-1	97,600	91,250	12.5%	99-101

Hardness patterns which indicate the extent of the strain hardening produced by the cold flow and the effect on the anneals are shown on the pages which immediately follow this text.

BY H. A. D. DATE 4/1/50  
 CHKD. BY DATE

SUBJECT Hand Press Survey  
Don't T306.5.10 Steel 1221  
Scale R.D. HT 44N294


SHEET NO. OF  
 JOB NO. V-337

2 e  
 91.75.95.95.95  
 80.74.84.85.85  
 76.77.77.77.79  
 78.81.79.83.85  
 79.90.90.92.92


2 e  
 64.68.74.81.85  
 72.78.77.77.81  
 71.74.82.72.72  
 73.75.80.75.75  
 79.78.78.80.78

2 e  
 85.86.88.88.90  
 87.92.92.92.85  
 88.91.90.93.91  
 89.83.81.82.82



As one  
 Backward Extrude



As one  
 1275° for 12 hrs.




As one  
 Forward Extrude





BY ALM DATE 11/8/54 SUBJECT TENSILE TEST SHEET NO.        OF         
 CHKD. BY        DATE        SPECIMEN        JOB NO.       

# $\frac{1}{2}$ " GAGE LENGTH TENSILE TEST SPECIMEN (FLAT)



OVERALL LENGTH OF SPECIMEN DEPENDENT  
 ON AMOUNT OF METAL AVAILABLE IN  
 PIECE FROM WHICH SPECIMEN IS MADE.

FACES OF SPECIMEN TO BE GROUND FLAT.  
 EDGES OF TEST SECTION MUST BE FREE OF  
 SCRATCHES.

THICKNESS OF SPECIMEN (T) GOVERNED  
 BY THICKNESS OF PIECE FROM WHICH  
 SPECIMEN IS MADE. SHOULD INCLUDE AS  
 MUCH OF WALL THICKNESS OF PIECE AS  
 POSSIBLE.

PROJECTILE, TARGET PRACTICE, 30MM, T328

## PROJECTILE, TARGET PRACTICE, 30MM, T328

### ENGINEERING CONSIDERATIONS

This shell body was similar to the T241 and T304 shell previously discussed in that it apparently should be manufactured using successive backward extrusion operations to form the two inside diameters.

Two factors only would prohibit such a procedure--excessively high reductions in area which would induce high stresses in the tools, or extremely low reductions which would not work harden the material to the degree necessary to develop the required yield strength.

The 47% reduction in area necessary to form the .825" upper diameter was not excessive and was certainly more than required to achieve a yield strength of 90,000 psi. The forming of the .663" lower diameter was less severe but still sufficient to develop the required mechanical properties from 1021 steel.

When a backward extrusion like the one used to form the .825" diameter was contemplated some thought had to be given to the limitation on the depth of extrusion imposed by the character of the lubricant. The area of the top surface of the preceding piece was stretched by backward extrusion to form the cavity and in some instances this surface might be stretched locally as much as 800%.

## PROJECTILE, TARGET PRACTICE, 30MM, T328

### ENGINEERING CONSIDERATIONS (Cont.)

As the depth of punch penetration increased, the surface metal and the lubricant increased in area. When this area increase thinned the coating too much it broke down, and the punch galled the work-piece.

This problem occurred when forming the upper diameter and it was necessary to extrude in two steps using an intermediate coating operation. In a special purpose surface treating operation, sufficient weight of coating probably could be applied to withstand the thinning produced by the total of these two operations.

Thus the basic forming operations consisted of three backward extrusions to form the cavity and outside diameter followed by a nosing operation to form the ogive.

Shearing was the most economical way to make billets from the bar stock, but it required an additional anneal to remove the effects of the severe cold work on the top and bottom surfaces, as well as a sizing operation to form the distorted slug into an acceptable shape for backward extrusion.

The basic sequence of operations was as follows:

1. Shear billets
2. Tumble
3. Anneal
4. Wheelabrate

## PROJECTILE, TARGET PRACTICE, 30MM, T328

### ENGINEERING CONSIDERATIONS (Cont.)

5. Surface treat
6. Size
7. Surface treat
8. Pre-backward extrude
9. Surface treat
10. First backward extrude
11. Surface treat
12. Second backward extrude
13. Nose
14. Stress relieve

In reaching the decisions outlined above a preliminary sequence of operations was prepared. When the thinking had crystallized and the volumetric relationships were calculated, a final drawing of the sequence of operations was made. This drawing #120472 is shown on the page immediately following this text.

The tooling required to extrude these pieces, and the gages necessary to measure them were then designed and built.

As the tools were tried out, and pieces made, there was considerable metallurgical experimentation to determine the optimum thermal treatment for both the process anneal and the final stress relief anneal.

These operations will now be discussed in detail with regard for practical considerations of a mechanical, metallurgical and productive nature.



## PROJECTILE, TARGET PRACTICE, 30MM, T328

### COLD FORMING OPERATIONS

#### 1. SHEAR BILLETS

The tooling required to shear the 1-1/4" diameter hot rolled bar is shown on Dwg #114782 which immediately follows the text on shell T241 and T304.

Random length bars were hand fed into the die during the up stroke of the press, and the billets were sheared to the proper weight of 4, 145 grains and fell out below the die.

With the exception of a tendency for galled metal to build up on the stop block, this operation was performed with little difficulty.

The die was set in a 100 ton crank press built by Verson Allsteel Press Company, although only 43 tons were actually required.

## PROJECTILE, TARGET PRACTICE, 30MM, T328

### COLD FORMING OPERATIONS (Cont.)

#### 2. TUMBLE BILLETS

This operation removed the sharp edges and burrs from the face of the billet.

To chamfer the distorted slug by mechanical means would have been difficult, and hand deburring was economically prohibitive. Tumbling offered an ideal solution to this problem in that it accomplished the objectives and required only a part-time operator to load and unload about one thousand (1,000) pieces every forty-five (45) minutes.



## PROJECTILE, TARGET PRACTICE, 30MM, T328

### COLD FORMING OPERATIONS (Cont.)

#### 3. ANNEAL BILLETS

Billets were heated in an electric furnace manufactured by The Lindberg Engineering Company to a temperature of 1250° F., soaked at this temperature for one and one-half (1-1/2) hours and air cooled.

A high but yet subcritical anneal such as this restored the original ductility to the sheared face of the billet without disturbing the structure of the steel. This thermal treatment also minimized the piece-to-piece differences in hardness which increased the repetitive accuracy of the forming operations.

## PROJECTILE, TARGET PRACTICE, 30MM, T328

### COLD FORMING OPERATIONS (Cont.)

#### 4. SHOTBLAST

The pieces, which were annealed in the presence of oxygen, scaled rather heavily. The best method of removing such a surface was mechanical blasting. This resulted in a surface which was clean and bright and which could be surface treated using the same chemical cycle employed to coat intermediate process pieces.

The pieces were placed in a gravity conveyor which fed them into the machine, where they were blasted and ejected automatically.

The wheelabrator used for this operation was the American Wheelabrator Corporation's tumble blast machine. When blasting annealed billets such as these it was important to use soft shot to prevent any imbedding of the shot in the relatively soft billets.

## PROJECTILE, TARGET PRACTICE, 30MM, T328

### COLD FORMING OPERATIONS (Cont.)

#### 5. SURFACE TREAT BILLETS

This surface treatment, or "Foscoating", operation was done on the Heintz experimental, manual Foscoat line. The pieces were placed in stainless steel trays by an operator and then the baskets were carried through the chemical cycle which follows:

1. Alkaline clean
2. Cold water rinse
3. Sulphuric acid pickle
4. Cold, overflowing water rinse
5. Hot, overflowing water rinse
6. Foscoat
7. Cold, overflowing water rinse
8. Hot, overflowing water rinse
9. Lubrication

Chemicals were supplied by Pennsylvania Salt Manufacturing Company of Philadelphia.

A complete description of the chemical constituents and process controls is contained in the appendix section entitled "Chemical Data".

PROJECTILE, TARGET PRACTICE, 30MM, T328

COLD FORMING OPERATIONS (Cont.)


6. SIZE BILLET

The tooling necessary to form this piece is shown on Dwg #B-119824 which immediately follows this text.

The Foscoated sheared slug was placed in the die and formed as shown on the above listed drawing. Great care had to be taken to properly align this die, as the impression made by the punch served as a guide for the backward extrusion punches which followed. If the die were misaligned, the piece would have been unalterably eccentric.

The shut height of the die had to be regulated to make the piece of the required size.

This die was run on a Verson 100 ton single point mechanical press. The required force for this operation was 118 tons.




NOTE

1. PUMP ASSEMBLY - 100% TESTED  
2. PUMP - 100% TESTED  
3. PUMP - 100% TESTED

HIGHLY POLISH BEFORE HARDENING & AFTER.  
MUST BE FREE OF NICKS, SCRATCHES & TOOL MARKS.


EDGE MUST BE HIGHLY POLISHED BEFORE HARDENING & AFTER.  
EDGE TO BE FREE OF NICKS & SCRATCHES.  
THERE ARE TO BE NO DEEP MARKS ON ANY SURFACE.

+000  
-000  
275 ± DA



BUSHING

MATERIAL - STAINLESS STEEL  
HARDEN R<sub>c</sub> 54-56




PUNCH

MATERIAL - STAINLESS STEEL  
HARDEN R<sub>c</sub> 59-60

22

HANGING PLUG

MATERIAL - 4015  
HARDEN - TOUGHEN





HERTZ MFG. CO.  
PHILADELPHIA, PA.

DIE PART DETAILS  
30MM T325 - FD-18088  
FRANKFORD ARSENAL

D-119824-1  
D-24294

4. Holes Read  
 90° Apart  
 1 2 3 4  
 Drill & Ream For  
 4 1/2 Dia Cap Screws  
 Note They Must Be  
 Body Bored  
 With Item # 2  
 Approx. 1/2 Dia AR  
 Vent To Line Up  
 With Item # 2  
 Drill & Ream For  
 4 1/2 In Dowel Pins  
 To Fit With Item # 2.



KNOCKOUT PIN  
 MATERIAL - STEEL  
 HDN RC 57 ST & 30-10

UPPER DIE SHOE  
 MATERIAL B.R.



A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V
HEINTZ MFG. CO. PHILADELPHIA, PA.												DATE JUL 27 1954		TIME 9 54		APPROVED JUL 27 1954		HEINTZ MFG. CO. 301 N. 12TH ST. PHILADELPHIA, PA. 19104		D-119824-2 24294	
FILE NO. CHANGE 108103 40 5-5 45095												108103 40 5-5 45095		108103 40 5-5 45095		108103 40 5-5 45095		108103 40 5-5 45095		108103 40 5-5 45095	





See drawing of 4.12.12 in Series  
 This Part Must Be Born Bored  
 To Item 1

See X Rays for 4.12.12  
 This Part Must Be Born Bored  
 To Item 1



3  
 3750 300201A  
 4 3 P 3  
 4 4

2) PUNCH RETAINER  
 PARTIAL

A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V
HEINTZ MFG. CO. PHILADELPHIA, PA.												DIE PARTS DETAIL SHEET SCHEMATIC T-226 - FD 10000 FRANKFORD ARSENAL		DIE NO 24294							
DRAWN 9.7.54												CHECKED E. L. 1-1-54		APPROVED							
FILE NO.												CHANGE									
DIE NO.												45015									
DIE NO.												100103									
DIE NO.												50 E		4016 S							
DIE NO.												METAL									

PROJECTILE, TARGET PRACTICE, 30MM, T328

COLD FORMING OPERATIONS (Cont.)

7. SURFACE TREAT

This operation was identical to Operation #5.

## PROJECTILE, TARGET PRACTICE, 30MM, T328

### COLD FORMING OPERATIONS (Cont.)

#### 8. PRE-BACKWARD EXTRUDE


This piece was formed in the tooling originally designed for the first backward extrusion. As previously explained, this extrusion was added to the sequence to compensate for the inability of the coating to withstand such deep punch penetration.

The alignment of this die was very important, in that it determined to a large extent the concentricity of the shell. The press shut height setting was not so critical as is generally true, since this operation was followed by first backward extrusion which finally formed the .820" diameter.

The tools are shown on Dwg #D-119825-4 which immediately follows the text describing the first backward extrusion. This operation differs from first backward extrusion only in the setting of press shut height.

The die was run on a Verson 100 ton single point mechanical press. The load required to form this piece was 78 tons.

163



NOTE:-

1. Parts 1 through 2345 - 23-16.17  
B 9 20 21 22 are NOT to be made
2. USE SIMILAR PARTS FROM DIE 23454  
Dwg. # 11111
3. Finish Table

HEWLETT PACKARD CO.		PART NUMBER		EXTENSION		Dwg. No.	
Palo Alto, CA		119825		B-119825		D-24295	
DATE		03/16/64		DATE		03/16/64	
BY		J. L. H.		BY		J. L. H.	
CHECKED		J. L. H.		CHECKED		J. L. H.	
APPROVED		J. L. H.		APPROVED		J. L. H.	

PROJECTILE, TARGET PRACTICE, 30MM, T328

COLD FORMING OPERATIONS (Cont.)

9. SURFACE TREAT

This operation was the same as operation #5 with the exception that a mechanical method of oscillating the pieces was used to allow the air to escape from the cavity.

## PROJECTILE, TARGET PRACTICE, 30MM, T328


### COLD FORMING OPERATIONS (Cont.)

#### 10. FIRST BACKWARD EXTRUDE

In this operation, as in all backward extrusions, the metal was stressed until it flowed up through the annular opening between punch and die.

The press shut heights had to be adjusted to make a piece with the desired base thickness of .870" plus or minus .005". The die had to be carefully aligned, and the piece, when made, had to be checked to see that the eccentricity did not exceed .010" TIR.

The tooling was set in a 100 ton Verson single point mechanical press and a force of 78 tons was necessary to extrude the metal. The tooling is described on Dwg #B-119825 which follows this text.



# NOTE:-

- 1- Parts Inventory 2345-1-17
- 2- Use Similar Parts From De 24294
- 3- From Date



167





[illegible]

1. Outer Ring 5000 ft. E. of base of hill
2. Inner Ring 5000 ft. E. of base of hill
3. Near Outer Ring 5000 ft. E. of base of hill
4. Near Outer Ring 5000 ft. E. of base of hill
5. Near Outer Ring 5000 ft. E. of base of hill
6. Near Outer Ring 5000 ft. E. of base of hill
7. Near Outer Ring 5000 ft. E. of base of hill

8  
2  
7  
3  
1

Shree Rung Asha  
Tens = 9 + 10



INNER Ring  
CLOCKWISE - 1st 4-5  
Hollow Ring 50-55 1000

[illegible]

DATE	TIME	NO.	DOE NO.	DOE NO.	DOE NO.
109103		4014-6		43096	B-119825-3
D-24295					

[illegible][illegible]

PROJECTILE, TARGET PRACTICE, 30MM, T328

COLD FORMING OPERATIONS (Cont.)

11. SURFACE TREAT

This surface treating procedure was identical to that described as operation #5.


COLD FORMING OPERATIONS (Cont.)

12. SECOND BACKWARD EXTRUDE

The .663" inside diameter was formed by this extrusion using the tooling shown on Dwg #B-119826 which immediately follows.

The Foscoated first backward extruded piece was placed in the die and forced down by the punch which then stressed the metal causing it to flow upward around the punch. The press setting was adjusted to give the proper bottom thickness of .322 to .328. The alignment of the die had to be consistent with an eccentricity requirement of .010" TIR. Enough metal was extruded in this die so that it flowed up and around the shoulder on the punch allowing the location of the inside shoulder of the piece to be positioned with great accuracy.

The die was set in a 100 ton Verson single point mechanical press. This extrusion actually required only 79 tons.



HEINTZ MFG. CO.  
PHILADELPHIA, PA.

HEINTZ MFG. CO. PHILADELPHIA, PA.		B-0-26	
FILE NO.	CHANGE	DATE	BY
1			
2			
3			
4			
5			
6			
7			
8			
9			
10			
11			
12			
13			
14			
15			
16			
17			
18			
19			
20			
21			
22			
23			
24			
25			
26			
27			
28			
29			
30			
31			
32			
33			
34			
35			
36			
37			
38			
39			
40			
41			
42			
43			
44			
45			
46			
47			
48			
49			
50			
51			
52			
53			
54			
55			
56			
57			
58			
59			
60			
61			
62			
63			
64			
65			
66			
67			
68			
69			
70			
71			
72			
73			
74			
75			
76			
77			
78			
79			
80			
81			
82			
83			
84			
85			
86			
87			
88			
89			
90			
91			
92			
93			
94			
95			
96			
97			
98			
99			
100			

173





10 1 1

6 112 2 00

2 4 3 2 1

1  
2

INNER RING  
MATERIAL: NUCLE WHTS  
HARDEN P. 50-52 & GR. 11

1875

Inner Ring

MATERIAL: MILK WHTS  
HARDEN P. 30-52 & GP. 12

(over) 6000

11

A. D. 1, 1922

[illegible]

227 6 0 0 0 0

[illegible]

A. J. C. B.



5 - 10 Employees 1,000 to 1,500 10 - 2000

*The Supreme Being*

7 STAND SUPPLY CO. 303 ALEX DR NW

MISSISSAUGA, Ont., July 10

Sweden P. vs. Assens.  
1721 9-2-10

[illegible]

**CHAMBERLAIN**

**DATE OF DEATH**

50	€	4016.7
----	---	--------

45097	
-------	--

**B-119826-3**

24296  
De 40

Page	Date	No.
1	10/10/10	1
2	10/10/10	2
3	10/10/10	3
4	10/10/10	4
5	10/10/10	5
6	10/10/10	6
7	10/10/10	7
8	10/10/10	8
9	10/10/10	9
10	10/10/10	10
11	10/10/10	11
12	10/10/10	12
13	10/10/10	13
14	10/10/10	14
15	10/10/10	15
16	10/10/10	16
17	10/10/10	17
18	10/10/10	18
19	10/10/10	19
20	10/10/10	20
21	10/10/10	21
22	10/10/10	22
23	10/10/10	23
24	10/10/10	24
25	10/10/10	25
26	10/10/10	26
27	10/10/10	27
28	10/10/10	28
29	10/10/10	29
30	10/10/10	30
31	10/10/10	31
32	10/10/10	32
33	10/10/10	33
34	10/10/10	34
35	10/10/10	35
36	10/10/10	36
37	10/10/10	37
38	10/10/10	38
39	10/10/10	39
40	10/10/10	40
41	10/10/10	41
42	10/10/10	42
43	10/10/10	43
44	10/10/10	44
45	10/10/10	45
46	10/10/10	46
47	10/10/10	47
48	10/10/10	48
49	10/10/10	49
50	10/10/10	50
51	10/10/10	51
52	10/10/10	52
53	10/10/10	53
54	10/10/10	54
55	10/10/10	55
56	10/10/10	56
57	10/10/10	57
58	10/10/10	58
59	10/10/10	59
60	10/10/10	60
61	10/10/10	61
62	10/10/10	62
63	10/10/10	63
64	10/10/10	64
65	10/10/10	65
66	10/10/10	66
67	10/10/10	67
68	10/10/10	68
69	10/10/10	69
70	10/10/10	70
71	10/10/10	71
72	10/10/10	72
73	10/10/10	73
74	10/10/10	74
75	10/10/10	75
76	10/10/10	76
77	10/10/10	77
78	10/10/10	78
79	10/10/10	79
80	10/10/10	80
81	10/10/10	81
82	10/10/10	82
83	10/10/10	83
84	10/10/10	84
85	10/10/10	85
86	10/10/10	86
87	10/10/10	87
88	10/10/10	88
89	10/10/10	89
90	10/10/10	90
91	10/10/10	91
92	10/10/10	92
93	10/10/10	93
94	10/10/10	94
95	10/10/10	95
96	10/10/10	96
97	10/10/10	97
98	10/10/10	98
99	10/10/10	99
100	10/10/10	100

**HEINTZ MFG. CO.**  
MILWAUKEE, WIS.  
30 MIN. - 325 - 50 0000  
OUR BEST SERVICE (C = 000)  
FRANKFORD, ILL.

[illegible]

1

<b>W</b>	<b>AB</b>	<b>A8</b>	
<b>X</b>	<b>AC</b>	<b>AM</b>	

[illegible]

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100
---	---	---	---	---	---	---	---	---	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	-----

[illegible]

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100
---	---	---	---	---	---	---	---	---	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	-----

U	O	
---	---	--

PROJECTILE, TARGET PRACTICE, 30MM, T328

COLD FORMING OPERATIONS (Cont.)

13. NOSE

The tooling built to form this piece is illustrated on Dwg #B-119847 and is the same die as was used to nose the T306E10 shell body.

The piece was placed mouth down in the die nest and formed as it was pushed down into the contained die. The distance between the mouth diameter and the bottom of the shell was controlled within the range of 2.720 to 2.740". On the return stroke of the press the piece was ejected from the die by a knockout pin.

This tooling was run on a 100 ton Verson mechanical press although the operation required only 16 tons.


COLD FORMING OPERATIONS (Cont.)

14. STRESS RELIEVE

The optimum stress relief temperature determined empirically was found to be 700° F. The pieces were held at this temperature for one and one-half (1-1/2) hours in a Lindberg Electric Furnace and air cooled. A discussion of the need for and the results obtained from this type of thermal treatment is found in the section entitled "Metallurgical Data and Discussion".

I C - E POSSIBLE  
 020  
 APPROX

1/8 APPROX  
 15/32 DIA



SHADED AREA TO BE MACHINED AWAY.  
 OTHER SURFACES ARE FINISHED

A	DATE	APPROVED	F	
B			G	
C			H	
D			J	
E			K	

HEINTZ MFG. CO. PHILADELPHIA, PA.		APPROXIMATE EXCESS METAL ON SHELL BODY FD-18088A 30MM T328 - FRANKFORD ARSENAL	
DRAWN JER 9-15-54	TRACED	CHECKED	APPROVED

E-119837

FILE NO. CHANGE

ASSEMBLIES ON UNIT

CUST. NO.

METAL

NO. REQ.

## PROJECTILE, TARGET PRACTICE, 30MM, T328

### MACHINING AND FINISHING OPERATIONS

These operations to be described hereafter were performed by Pantex Manufacturing Company, Pawtucket, Rhode Island, on high production machine tooling.


The operations were as follows:

1. Rough face and drill
2. Finish face, drill and ream
3. Machine and knurl band seat and machine band groove
4. Wash
5. Tap the .8750-20-UNEF-28 thread
6. Wash
7. Swage band
8. Machine band
9. Stencil
10. Phosphatize
11. Paint
12. Pack

A sketch illustrating the cold formed blanks and indicating the metal to be removed is shown on the following page.

A CUT F POSSIBLE  
020  
APPROX

1/8 APPROX



1 APPROX  
15/32 DIA  
1

SHADED AREA TO BE MACHINED AWAY.  
OTHER SURFACES ARE FINISHED

APPROXIMATE EXCESS METAL ON  
SHELL BODY FD-180BBA  
30MM T328 - FRANKFORD ARSENAL

HEINTZ MFG. CO.  
PHILADELPHIA, PA.

DRAWN  
JER  
9-15-54

APPROVED

APPROVED

E-119837

FILE NO. CHANGE

ASSEMBLIES ON UNIT

CUST. NO.

METAL

NO. REQ.

# PROJECTILE, TARGET PRACTICE, 30MM, T328

## MACHINING AND FINISHING OPERATIONS (Cont.)

### 1. ROUGH FACE AND DRILL

The open end of the cold formed blank was faced and the inside diameter in the area to be threaded was machined on a 1-5/8" New Britain Gridley six spindle automatic chucking machine. MOR-FILM, a soluble oil manufactured by L R Kerns Company, Chicago, Illinois, mixed with water in the ratio of 20:1 was used as a coolant.

The setup data for this operation is shown below in tabular form.

Machine:	1-5/8 New Britain Gridley	Spindle Gears:	45/87
Operation:	Drill & Face	Feed Gears:	47/85
Steel Spec:	1021	Tool Slide Cam Rise:	3/4
Collet Size:	1-3/16	Lower Front Form-	
SSFPM:	111	ing Slide:	7/32
Spindle RPM:	435	Motor:	15 HP,
Cycle:	19		220 V, 3
Hourly Prod:	185		phase, 60
			cycle

POS	TOOL SLIDE OPERATION	POS	CROSS SLIDE OPERATIONS
1		1	Face to length 2.770-2.780 form tool holder (std)
2	Drill using st'd 5/8 three lip stub drill	2	
3	Drill using st'd 11/16 three lip stub drill	3	
4		4	
5		5	
6	Insert shell using st'd aux- iliary operated inserter	6	Mount st'd gravity feed magazine in upper front forming slide.

# PROJECTILE, TARGET PRACTICE, 30MM, T328

## MACHINING AND FINISHING OPERATIONS (Cont.)

### 2. FINISH FACE, DRILL AND REAM

The pieces were next chucked in a 1-1/2" eight spindle Conematic and the above operations were performed.

The types of tools, tool position, speeds and feeds, etc., are shown below. Drawings illustrating all but standard tools are found on the pages immediately following this text.

Machine:	1-1/2 x 8 Conematic Chucker Serial #3319WW	Spindle Gears:	33/39
		Feed Gears:	34/44
		Tool Slide Cam Rise:	3/4
Operation:	Face, Drill, Ream	Front Cross Slide Cam Rise:	1/4
Steel Spec:	1021	Rear Cross Slide Cam Rise:	0
Collet Size:	1-3/16	Aux Cam Pos 6 Rise:	11/16
SSFPM:	92		
Spindle RPM:	361		
Cycle:	26		
Hourly Prod:	135		

POS TOOL SLIDE OPERATIONS		POS CROSS SLIDE OPERATIONS	
1	Drill using st'd 25/32 three lip stub drill	1	
2	Drill using st'd 13/16 three lip stub drill	2	
3		3	Face to 2.720-2.725 length using T-158-T-5 tool in T-158-T-11 tool holder
4	Ream minor pitch diameter using st'd 53/64 dia. (ground undersize to .823 dia.) 8 flute reamer	4	
5	Chamfer using st'd 1" dia. center drill	5	



PROJECTILE, TARGET PRACTICE, 30MM, T328

MACHINING AND FINISHING OPERATIONS (Cont.)


FINISH FACE, DRILL AND REAM (Cont.)

POS	TOOL SLIDE OPERATIONS	POS	CROSS SLIDE OPERATIONS
6	Ream front of .810 dia. cavity using st'd 13/16 dia. 8 flute reamer	6	
7	Insert shell using st'd aux- iliary operated inserter	7	Mount st'd gravity feed maga- zine
8		8	

The coolant was the E F Houghton Company's Antisep All Purpose Base mixed with water in the ratio of 20:1.

This machine was powered by a 25 HP, 220 volt, 60 cycle, 3 phase, 1750 RPM motor.

The tools are shown on drawings on the pages immediately following this text.



MARK TOOL NE, P.C. N9 & 30MA FA  
BREAK ALL UNNECESSARY SHARP EDGES

[illegible]

# PROJECTILE, TARGET PRACTICE, 30MM, T328

## MACHINING AND FINISHING OPERATIONS (Cont.)

### 3. TURN AND KNURL BAND SEAT AND FORM BAND GROOVE AND 1/8 RADIUS ON BOTTOM OF SHELL

A 1-1/2" eight spindle Conematic chucking machine was used for these operations. The necessary machine data as well as tool position and type are as follows:

Machine:	1-1/2 x 8 Conematic Chuckler, Serial #3319WW	Spindle Gears:	33/39
		Feed Gears:	34/44
		Tool Slide Cam Rise:	1/2
Operation:	Form band seat, groove, incl. knurl & form 1/8 radius on back	Front Cross Slide Cam Rise:	5/32
		Rear Cross Slide Cam Rise:	0
Steel Spec:	1021		
Collet Size:	1-3/16		
SSFPM:	110		
Spindle RPM:	361		
Cycle:	26		
Hourly Prod:	135		

POS TOOL SLIDE OPERATIONS		POS CROSS SLIDE OPERATIONS	
1		1	
2		2	Form 1/8 radius on back using dovetail form tool in st'd 39-3 splitter form tool holder
3		3	Form band seat groove (partial) using T-158-T-5 tool in T-158-T-11 tool holder
4		4	Form 15° band seat groove undercut using T-312E2-T-19 tool in M95-T-37 tool holder
5	Mount roll support using CX-15323 st'd tool holder	5	Knurl band seat with st'd 25P Reed knurling tool in M99-T-29 knurl holder

PROJECTILE, TARGET PRACTICE, 30MM, T328

MACHINING AND FINISHING OPERATIONS (Cont.)


TURN AND KNURL BAND SEAT AND FORM BAND GROOVE  
AND 1/8 RADIUS ON BOTTOM OF SHELL (Cont.)


POS	TOOL SLIDE OPERATIONS	POS	CROSS SLIDE OPERATIONS
6		6	
7	Insert shell using st'd auxiliary operated work inserter	7	Mount st'd gravity feed magazine
8		8	

Houghton's Antisep All Purpose Base, mixed with water in the ratio of 20:1, was the coolant.










A				F
B				G
C				H
D				J
E				K

HEINTZ MFG. CO. PHILADELPHIA, PA.				RADIUS TOOL USED BY PANTEX MFG. CO. CENTRAL FALLS R.I.		E-122728	
DRAWN J.B. BENSON 7-11-55		TRACED		CHECKED R. DEWITT 7-14-55		APPROVED BY 	TOOL NO. T 328-T-2





## PROJECTILE, TARGET PRACTICE, 30MM, T328

### MACHINING AND FINISHING OPERATIONS (Cont.)

#### 4. WASH

The machine used was a Blakeslee Metal Parts Washer of a single stage conveyor type, serial No 1138, manufactured by G S Blakeslee & Company of Chicago, Illinois.

The pieces were placed open end down in welded wire baskets which held fifty (50) pieces each. As the pieces were carried through the machine by the conveyor they were sprayed with an emulsion cleaner and a rust inhibitor.

The chemicals used were NAMUL (emulsion cleaner) and SR-12 (rust inhibitor) which were manufactured by the Angler Chemical Company, Norton, Massachusetts.

The NAMUL was mixed in the ratio of one (1) gallon to one hundred seventy-five (175) gallons of water and the SR-12 was used at the ratio of four (4) ounces to one hundred seventy-five (175) gallons of water. The temperature of the spray was maintained at 175° F.

PROJECTILE, TARGET PRACTICE, 30MM, T328

MACHINING AND FINISHING OPERATIONS (Cont.)

5. TAP 3/4" -20 THREAD

A Kaufman tapping machine, Serial #10-188, with a capacity of 5/8" to 1-1/8", manufactured by the L J Kaufman Manufacturing Company, Manitowok, Wisconsin, was used. The machine setup is listed below:

1. Motor: 3HP, 220 volts, 3 phase,  
60 cycle, 1725 RPM
2. Coolant: Trifalex (undiluted)
3. Production Rate: 200 pcs/hr.
4. Spindle Speed: 400 RPM
5. Lead Screw: 20 pitch, left hand

The operator placed two shell in the loading position of an eight station rotary table. The table then indexed and tapped two bodies simultaneously. While the machine operated, the operator removed two finished shell and replaced them with two new ones. The cycle was then repeated. An undiluted cutting oil manufactured by Trifalex Corporation of New York City was applied by brush to the area to be tapped.

PROJECTILE, TARGET PRACTICE, 30MM, T328  
MACHINING AND FINISHING OPERATIONS (Cont.)

6. WASH

This operation was identical to operation #4.

PROJECTILE, TARGET PRACTICE, 30MM, T328

MACHINING AND FINISHING OPERATIONS (Cont.)

7. SWAGE ROTATING BAND

A size 0 swaging machine manufactured by West Tire Setter Company, Rochester, New York, was used for this operation.

The shell was placed in the machine and its three jaws closed on the band, squeezed it into the band seat and around the knurls. A plug which closely fit the inside diameter was inserted in the shell to prevent collapse of the wall.

PROJECTILE, TARGET PRACTICE, 30MM, T328

MACHINING AND FINISHING OPERATIONS (Cont.)

8. MACHINE BAND

The band was formed on a Rapiduction Lathe type 601WD, manufactured by the Oster Manufacturing Company, Cleveland, Ohio.

The setup chart for this operation is shown below and tool drawings are found on the pages immediately following this text.

Collet Size:	1-3/16
Form Tool:	T-158-T-46
Tool Holder:	M-99-T-69
Spindle Speed:	1850 RPM
Coolant:	Houton Antisep 20:1
Manual Operation	

<div style="display: flex; justify-content: space-between;"> <div> <p>MAKE SHANK CRS CARBIDE GRADE 085</p> </div> <div> <p>FOR MACHINING 30 MM SHELL</p> </div> </div>													FILE NO.	CHANGE
<div style="display: flex; justify-content: space-between;"> <div> <p>ASSEMBLIES OR UNIT</p> <p>CUST NO.</p> <p>METAL</p> <p>NO REQ.</p> </div> <div> <p>E-122723</p> <p>T-158-T-46</p> </div> </div>														
<div style="display: flex; justify-content: space-between;"> <div> <p>HEINTZ MFG. CO. PHILADELPHIA, PA.</p> </div> <div> <p>FORM TOOL USED BY PANTEX MFG. CO. CENTRAL FALLS R.I.</p> </div> </div>														
<div style="display: flex; justify-content: space-between;"> <div> <p>DRAWN J.B. BENSON 7-12-56</p> </div> <div> <p>TRACED</p> </div> <div> <p>CHECKED P. G. G. G.</p> </div> <div> <p>APPROVED</p> </div> </div>														





PROJECTILE, TARGET PRACTICE, 30MM, T328  
MACHINING AND FINISHING OPERATIONS (Cont.)

9. STENCIL

A marking machine made by Noble & Westbrook Manufacturing Company, East Hartford, Connecticut, was used to stencil this shell.

Standard 1/16" high type was used to stencil at the rate of fifteen hundred (1500) pieces per hour.

The pieces were placed on the periphery of a large table which revolved slowly. Mounted on top of this table and on the same axis was a wheel of slightly smaller diameter which revolved at a slightly higher RPM than the table. As the table carried the pieces to the stationary stencil the wheel forced the piece against it. The stencilled pieces were automatically ejected from the machine.

## PROJECTILE, TARGET PRACTICE, 30MM, T328

### MACHINING AND FINISHING OPERATIONS (Cont.)

#### 10. PHOSPHATIZE FOR PAINT

The machine for the cleaning cycle used for this operation was a Blakeslee Metal Parts Washer of a single stage conveyor type, manufactured by G S Blakeslee & Company, Chicago, Illinois. The shell bodies were placed mouth down in welded wire baskets which held fifty (50) pieces each. As the pieces were carried through the machine by the conveyor they were sprayed with the cleaner.

The remaining operations were done by dipping the pieces in tanks which contained the various solutions. The baskets were moved from tank to tank using a one (1) ton Budgit Hoist.

The chemical cycle was as follows and conformed to MIL-C-490. Two thousand (2,000) pieces an hour were processed.

##### 1. Clean

Machine:	Blakeslee Metal Parts Washer
Chemical:	#420A Cleaner
Manufacturer:	Angler Chemical Company, Norton, Massachusetts
Composition:	8 lbs. of cleaner to 175 gal. of water
Temperature:	160° F.
Time:	4 min.
Type of Application:	Spray

PROJECTILE, TARGET PRACTICE, 30MM, T328

MACHINING AND FINISHING OPERATIONS (Cont.)

PHOSPHATIZE FOR FAINT (Cont.)

2. Rinse

Machine: 200 gallon tank  
Chemical: None  
Composition: None (water)  
Temperature: 180° F.  
Time: 1 min.  
Method of  
Application: Dip

3. Phosphate Coat

Machine: 250 gallon tank  
Chemical: Matabond #14  
Manufacturer: International Rust Proof Company of  
Cleveland, Ohio  
Composition: 32 point bath  
Temperature: 200° F.  
Time: 8 min.  
Method of  
Application: Dip

4. Rinse

Machine: 200 gallon tank overflowing  
Chemical: None  
Composition: Water  
Temperature: 205° F.  
Time: 1 min.  
Method of  
Application: Dip

PROJECTILE, TARGET PRACTICE, 30MM, T328  
MACHINING AND FINISHING OPERATIONS (Cont.)

PHOSPHATIZE FOR PAINT (Cont.)

5. Chromic Acid Dip

Machine:	200 gallon tank
Chemical:	D & I rinse
Manufacturer:	Doe & Ingalls, Inc., Everett, Mass.
Composition:	1 pint
Temperature:	210° F.
Time:	2 min.
Method of Application:	Dip

PROJECTILE, TARGET PRACTICE, 30MM, T328  
MACHINING AND FINISHING OPERATIONS (Cont.)

11. PAINT

Black lusterless enamel conforming to specification MIL-E-10687 was applied to the shell bodies by a Paasche air finishing machine, manufactured by Paasche Air Brush Company, Chicago, Illinois. This was a conveyor machine type 236. The conveyor had seventy-two spindles and the entire machine was capable of painting fifteen hundred (1500) shell per hour. The spray guns and pressure tanks were made by the deVilbiss Company of Toledo, Ohio.

The pieces were placed vertically with the open end up on the conveyor spindles and were carried around to the painting location. The shell started to rotate just before they reached the spray gun. Two spray guns were used. One was located above the shell and directed the paint spray along a line making a ten degree ( $10^{\circ}$ ) angle with the horizontal. The second gun was located under the piece and sprayed upward at a thirty degree ( $30^{\circ}$ ) angle. The pieces then passed through a drying tunnel which employed as a heat source fourteen (14) lamps which dissipated fourteen (14) Kilowatts.

# PROJECTILE, TARGET PRACTICE, 30MM, T328

## INSPECTION

The following list of gages was used to check this shell.

1. Length gage (press)	J-15146
2. Thread gage	J-15736
3. Crimp groove check	J-15709
4. O.D. of band 1.228" go	J-15710
5. Progressive snap gage for band O.D.	J-15711
6. Overall length 2.74"	J-15713
7. .980" Nose diameter	J-15715
8. .810-.825" plug gage	J-15719
9. .654-.664" plug gage	J-15720
10. .8209-.8287" plug gage	J-15737

All of these gages are standard with the exception of items #1 and 3. These gages are shown on Dwg #D-121116 and E-120470 on the following pages.

GAGE STOCK  $\frac{1}{4} \times 2\frac{1}{2} \times \frac{5}{16}$   
HON. & GAD.

3.11D.1  
 100.5  
 000.5

GAGE TO CHECK .030 DIA. CRIMPING GROOVE  
30MM T306 E10 & 30MM T328  
FRANKFORD ARSENAL

**HEINTZ MFG. CO.**  
**PHILADELPHIA, PA.**

DRAWN MD 3-7-55	TRACED	SEARCHED JOL 3-7-55
-----------------------	--------	---------------------------

**E-120470**

J-15709

# LIST OF MATERIALS

NOTE

QTY IN  
1000

ROUGH SIZE


QTY	IN	ROUGH SIZE
2	1	1/4 DIA. 3/16
3	1	2 1/4 DIA. 1/4
4	1	2 1/4 DIA. 3/16
5	1	3/4 DIA. 2 1/4
5	1	3/4 DIA. 3/4



1/4 DIA.

2 1/4 DIA.

±.0002  
477 DIA





2 1315

2 7205

2 315

±.002  
738 DIA

±.002  
650 DIA



MUST BE SHARP TO SIZE

±.0002  
5000 DIA

MUST BE SHARP  
TO SIZE

±.001  
650 DIA

1/2 DIA.

A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

HEINTZ MFG. CO.  
PHILADELPHIA, PA.

LENGTH 1.5  
WIDTH .75  
THICKNESS .125

D-121116

J-15146

FILE NO. CHANGE

APPROVED ON UNIT

CERT. NO. 108103

50 E 4016-12

METAL

NO. 45710

JIG NO.



PROJECTILE, TARGET PRACTICE, 30MM, T328  
PACK

The pieces were packed according to specification MIL-P-10025A.

The box was made from 1/8" double faced corrugated cardboard and was 12-3/4" long x 6-3/8" wide x 9-1/4" deep and held one hundred (100) shell bodies in two (2) layers of fifty (50) each. The individual bodies were placed inside the spaces created by a 1/32" thick smooth cardboard separator. This separator was of the egg crate variety and formed pockets to hold five (5) shell along the width and ten (10) shell along the length of the box. A flat piece of 1/8" double face corrugated cardboard was used to separate the layers.

## PROJECTILE, TARGET PRACTICE, 30MM, T328

### METALLURGICAL DATA AND DISCUSSION

This shell body, in common with the other three previously discussed, had mechanical property requirements of 90,000 psi minimum yield strength and an elongation of 10%.

The type steel, the metallurgical thinking, and procedures were identical to those employed on the T304 and T241 shell bodies. The only differences peculiar to this shell were the reduction in area and the resultant change in the stress relief temperature to 700° F.

The mechanical properties obtained using a 1/2" flat specimen are listed below:


<u>Specimen</u>	<u>Tensile Strength</u>	<u>Yld. Str. (.1% Off.)</u>	<u>Elong. in 1/2"</u>	<u>Hardness Range</u>
1-2	102,750	97,700	11.0%	99-104
2-2	103,300	97,600	12.5%	99-104

Hardness patterns illustrating the effects of cold working and both process and stress relief anneals appear on the page following this text.


BY H. A. D. DATE 4/7/55  
 CHKD. BY DATE  
 Frankford Arsenal

SUBJECT Hardness Survey  
 32 M.M. T 322 Steel 1041  
 Scale R.D. H<sup>100</sup> 47 N 294

SHEET NO. OF  
 JOB NO. V-42.16




Unannealed




1230°F Annealed

12 hours at heat  
 Liquid Erc for face




As hit

1st Backward Extrude




As hit

2nd Backward Extrude




As hit

Nose



Before stress relieving

Nose



As hit  
 Stress relieving  
 (700° for 2 hours)

## APPENDIX

### Chemical Data:

All cold forming operations of the severity described in this report require a lubricant that will withstand the extreme pressures. The importance of this lubricant cannot be over-emphasized and unless it is carefully controlled as outlined below, work pieces will be severely galled and eccentric.

### Surface Treatment - Procedure and Controls

1. Alkaline Cleaner  
Fosclean C-4, 6 oz. /gal., 200-210° F., 5 minutes
2. Cold, overflowing water rinse
3. Sulfuric Acid Pickle  
12% H<sub>2</sub>SO<sub>4</sub> by weight, 170° F., 4-5 minutes
4. Cold, overflowing water rinse
5. Hot, overflowing water rinse (160° F.)
6. Foscoat  
35 points, 180-185° F., 7 minutes
7. Cold, overflowing water rinse
8. Final hot rinse  
Fosrinse R-1, 0.1%, 160° F., 30-60 seconds
9. Lubrication  
Foslube L-19, 2.5% solids, 130-150° F., 3 minutes

Process:	Foscoat
Operation:	Alkaline Cleaning
Material:	Fosclean C-4, PennSalt Mfg. Co.

## APPENDIX (Cont.)

Tank Capacity:	361 gallons
Concentration:	6 oz. /gallon
Charge:	135 lbs. Fosclean C -4
Operating Instructions:	Immerse for 5 minutes at 200-210° F. Bath to be air agitated
Process:	Foscoat
Operation:	Pickling
Material:	Sulfuric Acid, 66° Baume, Sp. gr. 1.835
Tank Capacity:	363 gallons
Concentration:	10-12% by wt. 106-130 gms. H <sub>2</sub> SO <sub>4</sub> /liter
Charge:	26 gallons (2 carboys) Sulfuric Acid
Operating Instructions:	Immerse for 4-5 minutes at 170° F. Iron content should not exceed 4-5%
Process:	Foscoat
Operation:	Foscoat
Material:	Foscoat A, Z, AS, SG, PennSalt Mfg. Co.
Tank Capacity:	409 gallons

### 35 point bath

10.40 gallons (143 lbs.) Foscoat Z  
2.75 gallons (30.7 lbs.) Foscoat A  
8.20 lbs. Foscoat SG

## APPENDIX (Cont.)

### Alternative

7.26 gallons (92 lbs.) Foscoat AZ

6.05 gallons (84 lbs.) Foscoat Z

8.02 lbs. Foscoat SG

Operating Instructions: Immerse for 7 minutes at 180-185° F. Temperature must be regulated so that introduction of work load does not reduce temperature below 180° F. Work must be racked to permit escape of gas.

Process: Foscoat

Operation: Final Hot Rinse

Material: Foslub R-1, PennSalt Mfg. Co.

Tank Capacity: 560 gallons

Concentration: 0.1% by weight

Charge: 4.7 lbs. Foslub R-1

Operating Instructions: 30-60 seconds at 140-160° F.

Process: Foscoat

Operation: Lubrication

Material: Foslub L-19, PennSalt Mfg. Co.

Tank Capacity: 361 gallons

Concentration: 10% by wt. of the product (2.5% fat content)

Charge: 300 lbs. Foslub L-19

Operating Instructions: 3 minutes at 130-150° F.

# APPENDIX (Cont.)

## SUGGESTED PRESS EQUIPMENT TO MAKE SMALL CALIBER PROJECTILES FROM 20MM to 40MM

While as earlier noted, only five light presses--the heaviest being 250 tons at most--would be required to make the simpler 30mm projectiles, a desirable lineup of optimum utility is suggested below.

<u>OPERATION</u>	<u>TONNAGE &amp; DISTANCE UP FROM BOTTOM OF STROKE</u>	<u>SHUT HEIGHT ON TOP OF BOLSTER STROKE DOWN ADJ. UP</u>	<u>KNOCKOUT (See Note #4)</u>	<u>STROKE</u>
SHEAR	100 T, 1" up	14"	No	6"
FORMING	500 T, 1" up	30"	Yes	16"
FORMING	400 T, 2" up	30"	Yes	16"
FORMING	400 T, 2" up	30"	Yes	16"
FORMING	200 T, 2" up	30"	Yes	16"
FORMING	200 T, 2" up	30"	Yes	16"
FORMING	100 T, 1" up	30"	Yes	16"

### NOTES:

1. All Bed Areas: 30" x 30"
2. All Presses rated at 50 strokes per minute except the Shearing Press which should be rated at 125 strokes per minute
3. All Presses to have automatic feeding device
4. Knockout to have adjustable travel - 0" to 6" and 10% of rated press tonnage
5. All press rams to have 3" adjustment
6. Knockout Stroke Cycle:
  - a. Ram top dead center - Knockout up
  - b. Ram 90° forward - Knockout down
  - c. Knockout dwell down until ram is 5" up on return stroke
  - d. Ram 60° before top dead center - Knockout up
  - e. Knockout raised and dwelling for top 60° of ram cycle

## APPENDIX (Cont.)

### MATERIAL SPECIFICATIONS

Carbon or alloy steel for the production of these shell should be ordered as "Hot Rolled Bar Stock" to meet Federal Specification QQ-S-633. Knowing the end use of the steel and the process to be used, the fabricator and the steel mill can jointly determine specific requirements and precautions necessary to produce steel that will produce satisfactory finished pieces (and within the general AISI requirements for projectile quality steel).

Certain requirements have been developed which can serve as starting points in any such discussion. These points will be described briefly in the following paragraphs.

The steel should be bought in the "as-rolled" condition. It has been found that the lower carbon steels can be sized or backward extruded in the "as-rolled" condition.

Chemistry restrictions need not be any more rigid than called for under this Federal Specification with the possible exception of silicon. Our experience has indicated that a "Fully Aluminum Killed" steel is the best type to use for this work. In any event, it would be wise to limit the silicon content to .08 maximum.

Commercial tolerances for dimensions and reconditioning of bar stock are satisfactory.



## APPENDIX (Cont.)

The application of macroetch examination standards should be approached with caution. Certain obvious defects such as pipes, flakes, bursts, severe segregation, and deep surface defects are, of course, unacceptable. When it comes to various types of ingot patterns and segregation patterns, however, no clearly defined correlation with defects in finished pieces has been established. If such a correlation can be established, it should be negotiated with the steel mill.

Grain size should be 5 or finer (Ferritic).